

Title (en)

A device for direct electrostatic printing wherein the distance between the printhead structure and the surface of a charged toner conveyor is kept constant

Title (de)

Vorrichtung zum direkten, elektrostatischen Drucken, wobei der Abstand zwischen dem Druckkopf und der geladenen Toner-Oberfläche konstant gehalten wird

Title (fr)

Dispositif d'impression électrostatique directe, dans lequel la distance entre la tête d'impression et la surface du toner chargé est maintenue constante

Publication

**EP 1111478 A1 20010627 (EN)**

Application

**EP 99204397 A 19991220**

Priority

EP 99204397 A 19991220

Abstract (en)

A device for direct electrostatic printing wherein the distance between the printhead structure and the surface of the charged toner conveyor (a CTC) is kept constant by contacting the frame carrying the printhead structure with the surface of the CTC. The frame can be kept directly in contact with the surface of the CTC or over spacers inserted between the frame and the surface of the CTC. <IMAGE>

IPC 1-7

**G03G 15/34**; **B41J 2/415**

IPC 8 full level

**B41J 2/415** (2006.01); **G03G 15/34** (2006.01)

CPC (source: EP)

**B41J 2/4155** (2013.01); **G03G 15/346** (2013.01); **G03G 2217/0025** (2013.01)

Citation (search report)

- [XY] EP 0816944 A1 19980107 - AGFA GEVAERT NV [BE]
- [Y] US 5495273 A 19960227 - KITAMURA TETSUYA [JP]
- [Y] US 4318972 A 19820309 - HARDENBROOK JAMES M
- [X] US 5666147 A 19970909 - LARSON OVE [SE]

Designated contracting state (EPC)

AT CH CY DE DK ES FI GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

**EP 1111478 A1 20010627**

DOCDB simple family (application)

**EP 99204397 A 19991220**