

Title (en)
CURING OF RESINS

Title (de)
HÄRTUNG VON KUNSTSTOFFEN

Title (fr)
POLYMERISATION DE RESINES

Publication
EP 1112303 A2 20010704 (EN)

Application
EP 99946287 A 19990910

Priority
• GB 9902830 W 19990910
• GB 9819815 A 19980912
• GB 9909763 A 19990429

Abstract (en)
[origin: WO0015694A2] A method of manufacturing a product comprising at least two parts includes the steps of coating one of the parts at least partially with a resin having a trapped catalyst distributed therein, placing the parts together with the resin therebetween and releasing the catalyst into the resin to initiate curing at the desired time. The catalyst may be trapped either by encapsulation or by absorption/adsorption into the structure of a suitable substrate such as almond shell. The catalyst may be an organic peroxide, formic acid or toluene sulphonic acid. An accelerator may be used to accelerate curing.

IPC 1-7
C08J 3/24; **C08K 9/12**

IPC 8 full level
C08J 3/24 (2006.01); **C08K 5/00** (2006.01); **C08K 9/00** (2006.01); **C08K 9/10** (2006.01); **C08K 9/12** (2006.01); **C08L 101/00** (2006.01); **C09J 5/00** (2006.01); **C09J 11/00** (2006.01); **C09J 201/00** (2006.01)

CPC (source: EP)
C08J 3/241 (2013.01); **C08K 5/0025** (2013.01); **C08K 9/10** (2013.01); **C08K 9/12** (2013.01)

Citation (search report)
See references of WO 0015694A2

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
WO 0015694 A2 20000323; **WO 0015694 A3 20000713**; AU 5870799 A 20000403; CA 2343392 A1 20000323; CN 1325418 A 20011205; EP 1112303 A2 20010704; GB 9909763 D0 19990623; JP 2002524634 A 20020806; NO 20011212 D0 20010309; NO 20011212 L 20010309

DOCDB simple family (application)
GB 9902830 W 19990910; AU 5870799 A 19990910; CA 2343392 A 19990910; CN 99813045 A 19990910; EP 99946287 A 19990910; GB 9909763 A 19990429; JP 2000570228 A 19990910; NO 20011212 A 20010309