

Title (en)  
Device for covering the joints between floor coverings or the like

Title (de)  
Abdeckvorrichtung für Bodenbelagsfugen oder dergleichen

Title (fr)  
Dispositif pour recouvrir les joints des revêtements de sol ou similaires

Publication  
**EP 1114902 A2 20010711 (DE)**

Application  
**EP 00890350 A 20001124**

Priority  
AT 88999 U 19991222

Abstract (en)  
[origin: US2001005539A1] A cover apparatus (1) for flooring seam gaps comprises a mounting profile (2) and a cover strip (3), with the mounting profile (2) which can be fastened to the base (U) by way of a bridge element (5) along the seam gaps (F) or the like comprising at least one leg element (6) which projects upwardly from the bridge element (5) and can be joined together in a clamping manner with the cover strip (3). In order to enable the perfect insertion of the cover apparatus even in the case of a curved progress of the seam gap, a cover strip (3) is provided which consists of a flexionally yielding material and can be bent about axes parallel to the direction of insertion, which cover strip is associated as a mounting profile (2) made of deflection-resistant material with a profile rail (4) which is subdivided by transversally extending indentations (8) into sections (9) which can be mutually swiveled about axes (A) which are parallel to the direction of insertion.

Abstract (de)  
Eine Abdeckvorrichtung (1) für Bodenbelagsfugen umfaßt ein Halterungsprofil (2) und eine Abdeckleiste (3), wobei das über einen Stegteil (5) den Fugen (F) entlang am Untergrund (U) befestigbare Halterungsprofil (2) wenigstens einen vom Stegteil (5) hochragenden, mit der Abdeckleiste (3) klemmend zusammensteckbaren Schenkelteil (6) aufweist. Um die Abdeckvorrichtung auch bei einem bogenförmigen Fugenverlauf einwandfrei einsetzen zu können, ist eine aus biegeweichem Material bestehende und um steckrichtungsparelle Achsen biegsame Abdeckleiste (3) vorgesehen, der als Halterungsprofil (2) eine durch querverlaufende Einschnitte (8) in gegeneinander um steckrichtungsparelle Achsen (A) verschwenkbare Abschnitte (9) unterteilbare Profilschiene (4) zugehört. <IMAGE>

IPC 1-7  
**E04F 19/06**

IPC 8 full level  
**E04F 19/06** (2006.01)

CPC (source: EP US)  
**E04F 19/062** (2013.01 - EP US); **E04F 19/063** (2013.01 - EP US); **E04F 19/068** (2013.01 - EP US); **Y10T 428/197** (2015.01 - EP US); **Y10T 428/24008** (2015.01 - EP US); **Y10T 428/24198** (2015.01 - EP US)

Designated contracting state (EPC)  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)  
**EP 1114902 A2 20010711**; **EP 1114902 A3 20020731**; **EP 1114902 B1 20060614**; AT 4086 U1 20010125; AT E330094 T1 20060715; CN 1127600 C 20031112; CN 1306138 A 20010801; CZ 20004728 A3 20010815; DE 50012979 D1 20060727; DK 1114902 T3 20061023; ES 2265905 T3 20070301; HU 0004984 D0 20010228; HU 222416 B1 20030728; HU P0004984 A2 20020729; PL 204817 B1 20100226; PL 344730 A1 20010702; PT 1114902 E 20061031; SK 19342000 A3 20010806; SK 286361 B6 20080805; US 2001005539 A1 20010628; US 6550205 B2 20030422

DOCDB simple family (application)  
**EP 00890350 A 20001124**; AT 00890350 T 19991222; AT 88999 U 19991222; CN 00136091 A 20001222; CZ 20004728 A 20001215; DE 50012979 T 20001124; DK 00890350 T 20001124; ES 00890350 T 20001124; HU P0004984 A 20001220; PL 34473000 A 20001221; PT 00890350 T 20001124; SK 19342000 A 20001215; US 74196600 A 20001221