

Title (en)  
Burial crypt

Title (de)  
Grabkammer

Title (fr)  
Caveau funéraire

Publication  
**EP 1118737 A2 20010725 (DE)**

Application  
**EP 01107209 A 19920603**

Priority  
• DE 4118408 A 19910605  
• DE 9109652 U 19910803  
• DE 9109653 U 19910803  
• EP 92109351 A 19920603

Abstract (en)  
The lid of the grave chamber is formed as a trough (162) to be covered with earth. The trough is surrounded by pairs of support walls (181, 182) either directly or with spacing to form several chamber parts. One pair forms the longitudinal support walls (181) and one pair form the transverse support walls. The vertical spacing from the lower edge to the top edge of the chamber rings equals the length of one chamber ring and the spacing in the vertical above same is greater than the length of one chamber ring. Inside the support walls a group of chamber parts (161) makes up the chamber rings and spacers are provided at certain mutual spacing between the rings. The support walls have a height which is roughly equal to the sum of the height of the existing chamber rings or height of the trough.

Abstract (de)  
Die Grabkammer (160) weist einen ringsum geschlossenen Kammerteil in Form einer Bodenwanne (161) oder eines Kammerringes und einen Trog (162) auf. Der Kammerteil (161) nimmt bei einer Bestattung den Sarg auf. Der aufgesetzte Trog (162) verschließt den Kammerteil (161). Der Trog (162) enthält eine Erdbabdeckung. Es sind zwei Paar Stützwände (181, 182) vorhanden, die den einen Trog (162) oder die Tröge (162) mehrerer seitlich nebeneinander aufgereihter Kammerteile (161) außen ringsum in geringem Abstand umgeben. Die Längsstützwände (181) sind entlang der Schmalseite der Kammerteile (161) aufgestellt. Je eine Querstützwand (182) ist entlang der Längsseite des am Ende der Reihe gelegenen Kammerteils (161) aufgestellt. Die Stützwände (181, 182) sind so ausgebildet und angeordnet, daß sie im Höhenbereich von der Unterkante bis höchstens zur Oberkante des Kammerteils (161) an diesem anliegen und daß sie im darüber liegenden Höhenbereich einen bestimmten Abstand von der Außenseite des Troges (162) haben. <IMAGE>

IPC 1-7  
**E04H 13/00**

IPC 8 full level  
**E04H 13/00** (2006.01)

CPC (source: EP)  
**E04H 13/00** (2013.01)

Citation (applicant)  
DE 3537367 A1 19870423 - SUCKFUELL GERHARD, et al

Cited by  
EP1469145A1

Designated contracting state (EPC)  
AT BE CH DE DK FR LI NL

DOCDB simple family (publication)  
**EP 0528124 A1 19930224; EP 0528124 B1 20011024**; AT E207571 T1 20011115; DE 59209925 D1 20011129; EP 1118737 A2 20010725; EP 1118737 A3 20020123; EP 1118738 A2 20010725; EP 1118738 A3 20020123

DOCDB simple family (application)  
**EP 92109351 A 19920603**; AT 92109351 T 19920603; DE 59209925 T 19920603; EP 01107209 A 19920603; EP 01107210 A 19920603