

Title (en)

Plug pin for an internal combustion engine fuel injector nozzle

Title (de)

Ventilnadel für ein Brennstoffeinspritzventil einer Verbrennungsmaschine

Title (fr)

Aiguille pour un injecteur de carburant d'un moteur à combustion interne

Publication

EP 1136693 B1 20061102 (EN)

Application

EP 01106966 A 20010320

Priority

IT TO20000269 A 20000321

Abstract (en)

[origin: EP1136693A2] The nozzle (8) has a conical wall (13) with injection orifices (17); the pin (27) has a tip (38) activated by an axial force to engage the wall (13) and close the orifices (17); the tip (38) has a truncated-cone-shaped portion (41) having an outer surface (45) which rests entirely on the wall (13), possibly as a result of elastic deformation of the outer surface (45); and the outer surface (45) forms with the wall (13) a substantially zero angle with a tolerance of 0° to +/-10°. <IMAGE>

IPC 8 full level

F02M 61/04 (2006.01); **F02M 61/06** (2006.01); **F02M 61/12** (2006.01); **F02M 61/16** (2006.01); **F02M 61/18** (2006.01)

CPC (source: EP US)

F02M 61/04 (2013.01 - EP US); **F02M 61/06** (2013.01 - EP US); **F02M 61/12** (2013.01 - EP US); **F02M 61/1806** (2013.01 - EP US); **F02M 61/1873** (2013.01 - EP US)

Citation (examination)

- EP 1034371 B1 20041117 - SIEMENS AG [DE]
- WO 0019088 A1 20000406 - SIEMENS AG [DE], et al

Cited by

CN100400850C; US7331537B2; US7143964B2; WO2004085832A1; WO03098031A1; WO2004070198A1; WO2004044414A1

Designated contracting state (EPC)

DE ES FR GB IT SE

DOCDB simple family (publication)

EP 1136693 A2 20010926; **EP 1136693 A3 20020403**; **EP 1136693 B1 20061102**; DE 60124165 D1 20061214; DE 60124165 T2 20070906; ES 2272368 T3 20070501; IT 1319988 B1 20031112; IT TO20000269 A0 20000321; IT TO20000269 A1 20010921; US 2001054656 A1 20011227; US 6666388 B2 20031223

DOCDB simple family (application)

EP 01106966 A 20010320; DE 60124165 T 20010320; ES 01106966 T 20010320; IT TO20000269 A 20000321; US 81423001 A 20010321