

Title (en)

Device and method for reducing delay jitter in data transmission

Title (de)

Verfahren und Einrichtung zur Reduktion des Verzögerungsjitters in der Datenübertragung

Title (fr)

Méthode et dispositif pour la réduction de la gigue à retard dans la transmission de données

Publication

**EP 1143671 A2 20011010 (EN)**

Application

**EP 01107831 A 20010406**

Priority

JP 2000106779 A 20000407

Abstract (en)

A delay unit 103 adds holding time that has been set by a holding time setting unit 104 to a received data. The holding time is computed based on delay time of received data and the minimum delay time of data received up to a certain point for the purpose of reducing a total delay time. The delay time is estimated in a delay time estimating unit 106 from the difference between a reception time of a packet counted based on an internal clock generator 107 and a time designated by a time stamp in the received packet. <IMAGE>

IPC 1-7

**H04L 12/56**; **H04L 29/06**

IPC 8 full level

**H04L 12/64** (2006.01); **H04L 47/2416** (2022.01)

CPC (source: EP US)

**H04L 12/6418** (2013.01 - EP US); **H04L 47/10** (2013.01 - EP US); **H04L 47/2416** (2013.01 - EP US); **H04L 47/28** (2013.01 - EP US); **H04L 65/1101** (2022.05 - US); **H04L 65/80** (2013.01 - EP US); **H04L 2012/6472** (2013.01 - EP US); **H04L 2012/6489** (2013.01 - EP US)

Cited by

CN101958813A; EP1528724A4; EP2882120A1; US7558868B2; US9596072B2; JP2015065527A

Designated contracting state (EPC)

DE GB

DOCDB simple family (publication)

**EP 1143671 A2 20011010**; **EP 1143671 A3 20030521**; **EP 1143671 B1 20040721**; CN 1200539 C 20050504; CN 1321026 A 20011107; DE 60104353 D1 20040826; DE 60104353 T2 20050721; US 2002009054 A1 20020124; US 6985501 B2 20060110

DOCDB simple family (application)

**EP 01107831 A 20010406**; CN 01116279 A 20010409; DE 60104353 T 20010406; US 82763901 A 20010406