

Title (en)  
ELECTROMAGNETIC EXPOSURE CHAMBER FOR IMPROVED HEATING

Title (de)  
ELEKTROMAGNETISCHE STRAHLUNG EXPOSITIONSKAMMER FÜR VERBESSERTE HEIZUNG

Title (fr)  
CHAMBRE ASSURANT UNE EXPOSITION ELECTROMAGNETIQUE A CHAUFFAGE AMELIORE

Publication  
**EP 1145601 A1 20011017 (EN)**

Application  
**EP 98963029 A 19981216**

Priority  
US 9826215 W 19981216

Abstract (en)  
[origin: WO0036879A1] The present invention utilizes dielectric slabs to provide a relatively uniform electromagnetic field to a cavity between two or more dielectric slabs. Each dielectric slab is a thickness equal to or nearly equal to a quarter of a wavelength of the electromagnetic field in the dielectric slab. In a particular embodiment, sample material is introduced into the cavity between the two dielectric slabs. This sample material may be introduced through one or more openings in the dielectric slabs. In further embodiments, specialized choke flanges prevent the leakage of energy from this cavity. In a preferred embodiment, an elliptical conducting surface directs the electromagnetic field to a focal region between the two dielectric slabs. Openings to this focal region allow sample material to be passed through this region of focused heating.

IPC 1-7  
**H05B 6/78**; **H05B 6/70**

IPC 8 full level  
**H05B 6/70** (2006.01); **H05B 6/74** (2006.01); **H05B 6/76** (2006.01); **H05B 6/78** (2006.01)

CPC (source: EP)  
**H05B 6/701** (2013.01); **H05B 6/705** (2013.01)

Citation (search report)  
See references of WO 0036879A1

Designated contracting state (EPC)  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)  
**WO 0036879 A1 20000622**; AT E295060 T1 20050515; AU 1814199 A 20000703; AU 771172 B2 20040318; CA 2355152 A1 20000622; CA 2355152 C 20080722; DE 69830083 D1 20050609; DE 69830083 T2 20051006; EP 1145601 A1 20011017; EP 1145601 B1 20050504; JP 2002532864 A 20021002

DOCDB simple family (application)  
**US 9826215 W 19981216**; AT 98963029 T 19981216; AU 1814199 A 19981216; CA 2355152 A 19981216; DE 69830083 T 19981216; EP 98963029 A 19981216; JP 2000589005 A 19981216