

Title (en)
HEAT RESISTANT FIREPROOF MATERIAL AND VARIANTS

Title (de)
HITZEBESTÄNDIGES, FLAMMHEMMENDES MATERIAL UND VARIANTEN

Title (fr)
MATERIAU IGNIFUGE PROTEGEANT CONTRE LA CHALEUR ET VARIANTES

Publication
EP 1147719 A2 20011024 (EN)

Application
EP 99928269 A 19990610

Priority

- RU 9900195 W 19990610
- RU 98114006 A 19980731

Abstract (en)

The invention relates to multilayer protective materials used to sew clothes for firemen and rescue workers operating in areas of high temperature and open fire, and may be used in the manufacture of other articles, such as capes, covers, and blankets, which must show increased heat resistance for operation in areas of intense heat radiation and also open fire during fire suppression, including the suppression of burning sources of oil, gas and other substances. The essence of the invention is that in a heat-resistant fireproof material comprising a heat-resistant fiber substrate and a layer of moisture-resistant material with a metal coating layer applied thereon, according to the invention, the layer of moisture-resistant material is made of two layers, one of which comprises a sterically linked polymer having a liquid diffusion coefficient equal to or less than 10^{-9} cm²/sec, the other--a hermetic layer--is made of a rubber-based elastomeric material. In accordance with a variant of the invention, it comprises a porous material selected from the group consisting of polyolefins, fluorine-, chlorine- or silicon-containing polymers with a pore size of 0.01-1.0 μ m as the layer of moisture-resistant material, and aluminum, copper, titanium nitride with a layer thickness of 0.05-0.25 μ m as the metal coating layer. The technical result which is achieved when the invention is carried out is enhancement of the comfort of protective clothes made of the proposed material, which is due to the creation of conditions ensuring the removal of vapors of surplus moisture of the body directly through the heat-resistant material, enhancement of the fire resistant properties, which is due to an increase of the resistance to the action of open fire, preservation of the strength of the material within the period of heat action, an increase of the service life of the clothes, and also simplification of the structure of the material for sewing the clothes, enhancement of its operating properties and effectiveness of the protective action.

IPC 1-7
A41D 31/00; **A62B 17/00**; **B32B 5/18**; **B23B 27/06**

IPC 8 full level
B32B 7/02 (2006.01); **A41D 13/00** (2006.01); **A41D 31/00** (2006.01); **A62B 17/00** (2006.01); **B32B 27/06** (2006.01); **C09K 21/00** (2006.01)

CPC (source: EP)
A41D 31/085 (2019.01); **A62B 17/003** (2013.01)

Cited by
CN101987660A; EP1952980A3; WO2007014056A3; WO2013074133A1; US7682997B2; WO2007014056A2

Designated contracting state (EPC)
DE FR GB IT SE

DOCDB simple family (publication)
EP 1147719 A2 20011024; **EP 1147719 A4 20011024**; **EP 1147719 B1 20030226**; CN 1106274 C 20030423; CN 1311733 A 20010905; DE 69905620 D1 20030403; DE 69905620 T2 20040325; RU 2136504 C1 19990910; WO 0009213 A2 20000224; WO 0009213 A3 20000602; WO 0009213 B1 20000713

DOCDB simple family (application)
EP 99928269 A 19990610; CN 99809162 A 19990610; DE 69905620 T 19990610; RU 98114006 A 19980731; RU 9900195 W 19990610