

Title (en)

Method and device for driving a printing press with two individual drives

Title (de)

Verfahren und Vorrichtung zum Betreiben einer Druckmaschine mit zwei Einzelantrieben

Title (fr)

Méthode et dispositif de fonctionnement d'une machine d'impression avec deux entraînements individuels

Publication

EP 1149697 A3 20020821 (DE)

Application

EP 01108659 A 20010406

Priority

- DE 10017525 A 20000410
- DE 10115546 A 20010328

Abstract (en)

[origin: EP1149697A2] The method involves measuring the angular position of the wheel train at two different points, whereby the position of an individual drive (9,10) is set depending on the difference resulting from the angular settings. The measurement is made before the start of a printing process in a predetermined operating state and the drives are biased by the difference during printing. Independent claims are also included for the following: a drive for a printing machine.

IPC 1-7

B41F 13/14; B41F 13/004; B41F 13/012

IPC 8 full level

B41F 13/004 (2006.01)

CPC (source: EP)

B41F 13/0045 (2013.01)

Citation (search report)

- [YA] DE 19826338 A1 19990401 - HEIDELBERGER DRUCKMASCH AG [DE]
- [YA] EP 0904934 A1 19990331 - HEIDELBERGER DRUCKMASCH AG [DE]
- [A] EP 0592850 A1 19940420 - HEIDELBERGER DRUCKMASCH AG [DE]
- [A] DE 4210989 A1 19931007 - HEIDELBERGER DRUCKMASCH AG [DE]
- [AD] DE 4210988 A1 19931007 - HEIDELBERGER DRUCKMASCH AG [DE]
- [A] EP 0846555 A1 19980610 - ROLAND MAN DRUCKMASCH [DE]

Cited by

DE102007039221A1; EP1759842A3; CN116946790A; EP1759842A2

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)

EP 1149697 A2 20011031; EP 1149697 A3 20020821; EP 1149697 B1 20101110

DOCDB simple family (application)

EP 01108659 A 20010406