

Title (en)
Lip seal

Title (de)
Wellendichtung

Title (fr)
Joint à lèvres

Publication
EP 1152177 A3 20031112 (EN)

Application
EP 01110517 A 20010428

Priority
JP 2000133233 A 20000502

Abstract (en)
[origin: EP1152177A2] A lip seal comprises an elastomer lip member (12) having its rear supported with a pressure resisting back-up ring (13), and a synthetic resin lip member (14) arranged on a rear side of the elastomer lip (12). On the inner circumferential surface of the seal lip portion (124) of the elastomer lip member (12), helical grooves (125) generating a pumping action of a fluid introducing direction from an inner space (S1) of machine side when a shaft (2) rotates are formed. When a pressure in the inner space (S1) of machine is 1 MPa, by making a contact width between the seal lip portion (124) of the elastomer lip member (12) and a shaft (2) at least 0.6 mm, so that a surface pressure maximum portion of the seal lip portion (124) of the elastomer lip member (12) to the shaft (2) is biased or maldistributed toward its rear side, whereby a fluid introduction by said helical grooves (125) is performed satisfactorily (Fig. 1). <IMAGE>

IPC 1-7
F16J 15/32

IPC 8 full level
F16J 15/3232 (2016.01); **F16J 15/3244** (2016.01)

CPC (source: EP US)
F16J 15/322 (2013.01 - EP US); **F16J 15/3232** (2013.01 - EP US); **F16J 15/3244** (2013.01 - EP US)

Citation (search report)

- [X] EP 0926408 A2 19990630 - EAGLE IND CO LTD [JP]
- [E] EP 1134466 A2 20010919 - EAGLE IND CO LTD [JP], et al
- [A] EP 0851159 A1 19980701 - TOYODA AUTOMATIC LOOM WORKS [JP]
- [X] PATENT ABSTRACTS OF JAPAN vol. 2000, no. 05 14 September 2000 (2000-09-14)

Cited by
EP1731804A1; EP1840426A3; EP1304515A3; EP1840426A2

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)
EP 1152177 A2 20011107; **EP 1152177 A3 20031112**; JP 2001317635 A 20011116; US 2002003337 A1 20020110; US 6517082 B2 20030211

DOCDB simple family (application)
EP 01110517 A 20010428; JP 2000133233 A 20000502; US 84583201 A 20010501