

Title (en)
METHOD FOR OPTIMISING THE OPERATION OF A BLAST FURNACE

Title (de)
PROZESSOPTIMIERUNG EINES HOCHOFENS

Title (fr)
PROCEDE D'OPTIMISATION DU FONCTIONNEMENT D'UN HAUT FOUR

Publication
EP 1154825 B1 20031008 (FR)

Application
EP 99964668 A 19991223

Priority
• EP 9910348 W 19991223
• LU 90333 A 19981223

Abstract (en)
[origin: WO0038496A3] The invention concerns a method for optimising the operation of a tank furnace comprising nozzles which consists in making fine particles of prereduced ore. The fine particles of prereduced ore are mixed with a solid carbon reducing agent, the fine prereduced ore particles having a size distribution less than 2 mm and the solid carbon reducing agent having a size distribution less than 200 μ m. The mixture is injected hot through the nozzles into the tank furnace, wherein the fusion of the prereduced ore particles takes place.

IPC 1-7
B01D 1/00

IPC 8 full level
C21B 5/02 (2006.01); **F27B 1/16** (2006.01)

CPC (source: EP)
C21B 5/023 (2013.01); **F27B 1/16** (2013.01)

Designated contracting state (EPC)
AT DE GB IT NL

DOCDB simple family (publication)
WO 0038496 A2 20000706; WO 0038496 A3 20011108; AT E251487 T1 20031015; AU 3043200 A 20000731; DE 69912003 D1 20031113; DE 69912003 T2 20040805; EP 1154825 A1 20011121; EP 1154825 B1 20031008; LU 90333 B1 20000719; TW 473546 B 20020121

DOCDB simple family (application)
EP 9910348 W 19991223; AT 99964668 T 19991223; AU 3043200 A 19991223; DE 69912003 T 19991223; EP 99964668 A 19991223; LU 90333 A 19981223; TW 88107016 A 19990430