

Title (en)

CRIMPING RING AND METHOD FOR MAKING SAME

Title (de)

KLEMMRING UND VERFAHREN ZUR HERSTELLUNG

Title (fr)

BAGUE A RETREINDRE ET SON PROCEDE DE FABRICATION

Publication

EP 1156896 B1 20021120 (FR)

Application

EP 00907723 A 20000225

Priority

- FR 0000470 W 20000225
- FR 9902477 A 19990226

Abstract (en)

[origin: FR2790214A1] The invention concerns a crimping ring comprising a metal strip (10) wound on itself. One first linking element arranged at the first end (12) comprises a first surface (16) overlying an indentation and at least a female member (18) hollowed out from said first surface. A second linking element provided at the second end (14) comprises a second surface (20) overlying an indentation and a male member (22) shaped by a projection from said second surface. To produce the link, the male member (22) is engaged in the female member (18) and fixed thereto, while the overlying surfaces (16, 20) are arranged against each other so as to define a linking zone whereof the thickness is substantially equal to the current thickness of the strip.

IPC 1-7

B21D 39/03; **B21D 53/16**

IPC 8 full level

B21D 53/36 (2006.01)

CPC (source: EP US)

B21D 53/36 (2013.01 - EP US); **Y10T 24/1457** (2015.01 - EP US); **Y10T 24/1463** (2015.01 - EP US); **Y10T 24/1467** (2015.01 - EP US); **Y10T 24/1469** (2015.01 - EP US); **Y10T 24/148** (2015.01 - EP US); **Y10T 24/1488** (2015.01 - EP US)

Cited by

DE102014115727B3; WO2016066720A1; US10835946B2

Designated contracting state (EPC)

DE ES GB IT SE

DOCDB simple family (publication)

FR 2790214 A1 20000901; **FR 2790214 B1 20010518**; AU 2921600 A 20000914; DE 60000821 D1 20030102; DE 60000821 T2 20030904; EP 1156896 A1 20011128; EP 1156896 B1 20021120; ES 2185569 T3 20030501; US 6481061 B1 20021119; WO 0050183 A1 20000831

DOCDB simple family (application)

FR 9902477 A 19990226; AU 2921600 A 20000225; DE 60000821 T 20000225; EP 00907723 A 20000225; ES 00907723 T 20000225; FR 0000470 W 20000225; US 91407101 A 20010823