

Title (en)

Downdraft burner with secondary air supply

Title (de)

Sturzbrandbrennkammer mit Sekundärluftzuführung

Title (fr)

Brûleur à tirage inversé avec amenée d'air secondaire

Publication

EP 1158241 A3 20011219 (DE)

Application

EP 01112182 A 20010518

Priority

AT 9172000 A 20000525

Abstract (en)

[origin: EP1158241A2] The combustion chamber for a downdraft heating system has a multi-part structure with lateral covering bricks (4) and left and right longitudinal cover bricks (2,3). The cover bricks, together with a ceramic plate, form the incandescent fuel bed. A half section of the burning passage channel is scooped out of each longitudinal brick. The secondary air channels are recessed between the longitudinal cover bricks and the heat-resistant grid (5). The grid extends as far as the inner wall of the boiler, with a groove around it to take the sealing (6).

IPC 1-7

F23B 7/00; **F23H 17/08**; **F23L 9/00**; **F23M 5/02**

IPC 8 full level

F23H 17/08 (2006.01); **F23L 9/00** (2006.01); **F23M 5/00** (2006.01); **F23M 5/02** (2006.01)

CPC (source: EP US)

F23B 7/005 (2013.01 - EP); **F23H 17/08** (2013.01 - EP); **F23L 9/00** (2013.01 - EP US); **F23M 5/02** (2013.01 - EP)

Citation (search report)

- [XAY] EP 0154956 A2 19850918 - UNICAL SPA [IT]
- [Y] EP 0268208 A2 19880525 - KUENZEL KG PA KUE WERK [DE]
- [A] DE 4007849 A1 19910919 - HOFMANN HERMANN [DE]
- [A] FR 2592944 A1 19870717 - ETUDE APPLIC GLE ELEMENTS MECA [FR]
- [A] FR 2589988 A1 19870515 - KEDLER TARM AS HS [DK]

Cited by

AT505296B1; DE102008013891B4; DE102008013891A1

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)

EP 1158241 A2 20011128; **EP 1158241 A3 20011219**; **EP 1158241 B1 20041103**; AT 412235 B 20041125; AT A9172000 A 20040415; AT E281631 T1 20041115; DE 50104352 D1 20041209

DOCDB simple family (application)

EP 01112182 A 20010518; AT 01112182 T 20010518; AT 9172000 A 20000525; DE 50104352 T 20010518