

Title (en)
MARKING FILM AND COMPOSITE MARKING FILM

Title (de)
MARKIERUNGSFOLIE UND VERBUNDMARKIERUNGSFOLIE

Title (fr)
FILM DE MARQUAGE ET FILM DE MARQUAGE COMPOSITE

Publication
EP 1161348 A1 20011212 (EN)

Application
EP 00913576 A 20000222

Priority
• JP 6713899 A 19990312
• US 0004567 W 20000222

Abstract (en)
[origin: WO0054980A1] A marking film exhibiting good ability for tracing curved surfaces when it is to be stuck to steeply curved three-dimensional portions without entrapping air bubbles at the film edges when an over-clear coating is applied thereon after it has been stuck. The marking film has a marking component to be transferred onto an article via an adhesive layer, wherein the total thickness of the marking film is in the range of from about 50 μm to about 300 μm , and the modulus of elasticity thereof is in the range of from about 2 kgf/mm² to about 25 kgf/mm² as measured under a condition where the marking film is elongated at a tension speed of 300 mm/min. into an elongation percentage in the range of 0 to about 10 %.

IPC 1-7
B41M 3/12; **B44C 1/17**; **B44C 1/10**

IPC 8 full level
B41M 3/12 (2006.01); **C09J 7/02** (2006.01); **C09J 121/00** (2006.01); **C09J 133/00** (2006.01); **C09J 201/00** (2006.01); **B41M 5/00** (2006.01); **B41M 5/40** (2006.01); **B41M 5/41** (2006.01); **B41M 5/50** (2006.01)

CPC (source: EP)
B41M 3/12 (2013.01); **B41M 5/41** (2013.01); **B41M 5/508** (2013.01)

Citation (search report)
See references of WO 0054980A1

Cited by
EP3643364A1; WO2020083955A1; EP3643365A1; WO2020083954A1

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
WO 0054980 A1 20000921; AU 3499700 A 20001004; DE 60022990 D1 20060216; EP 1161348 A1 20011212; EP 1161348 B1 20051005; JP 2000265123 A 20000926

DOCDB simple family (application)
US 0004567 W 20000222; AU 3499700 A 20000222; DE 60022990 T 20000222; EP 00913576 A 20000222; JP 6713899 A 19990312