

Title (en)

METHOD FOR FEEDING IN AND STARTING A THREAD AND FALSE TWIST TEXTURING DEVICE

Title (de)

VERFAHREN ZUM EINFÜHREN UND ANLEGEN VON GARN UND FALSCHDRALLTEXTURIEREINRICHTUNG

Title (fr)

PROCEDE D'INSERTION ET D'ETALEMENT DE FIL, ET DISPOSITIF DE TEXTURATION PAR FAUSSE TORSION

Publication

EP 1161580 A1 20011212 (DE)

Application

EP 00912468 A 20000216

Priority

- DE 19906325 A 19990216
- DE 19909380 A 19990304
- EP 0001264 W 20000216

Abstract (en)

[origin: US6735934B1] A process and device for texturing a thread within a false twist texturing device with a heat exchanger having thread passages formed by thread passage segments. The heat exchanger possesses a first section and a second section which form a chamber into which a fluid can flow to treat a thread during operation of the heat exchanger. The first and second sections of the heat exchanger can be manipulated to enlarge the thread passages to facilitate insertion of the thread. After the thread insertion, the heat exchanger is sealable in such a manner that the thread passages seal around the thread to prevent leakage of the fluid from the chamber while allowing the thread to be movable through the heat exchanger.

IPC 1-7

D02J 13/00; D02G 1/02; D02J 1/08; B65H 51/16; D06B 23/18

IPC 8 full level

D02G 1/04 (2006.01); **D02G 1/02** (2006.01); **D02G 1/16** (2006.01); **D02J 1/08** (2006.01); **D02J 13/00** (2006.01)

CPC (source: EP US)

D02G 1/0273 (2013.01 - EP US); **D02G 1/161** (2013.01 - EP US); **D02J 1/08** (2013.01 - EP US); **D02J 13/006** (2013.01 - EP US)

Citation (search report)

See references of WO 0049212A1

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

US 6735934 B1 20040518; AU 3422700 A 20000904; CN 1323202 C 20070627; CN 1340114 A 20020313; EP 1161580 A1 20011212; EP 1161580 B1 20040714; JP 2002537494 A 20021105; WO 0049212 A1 20000824

DOCDB simple family (application)

US 91348901 A 20011213; AU 3422700 A 20000216; CN 00803764 A 20000216; EP 0001264 W 20000216; EP 00912468 A 20000216; JP 2000599931 A 20000216