

Title (en)

Insulating compound profile, in particular for windows, doors, facades or the like

Title (de)

Wärmegedämmtes Verbundprofil, insbesondere für Fenster, Türen, Fassaden und dergleichen

Title (fr)

Profilé composite calorifuge, notamment pour fenêtres, portes, façades et similaires

Publication

**EP 1170454 B1 20080716 (DE)**

Application

**EP 01112511 A 20010523**

Priority

DE 10033388 A 20000708

Abstract (en)

[origin: EP1980701A1] Composite profile comprises metal profiles (1, 2) joined to each other by single insulating strips (3) via connecting bars (5). Preferred Features: The wall thickness of the single insulating strips is 0.5-1.5 mm, preferably 0.6-1.0 mm. The connecting bars are aligned perpendicular to the single insulating strips. The distance between the metal profiles and the connecting zone of the connecting bars on the single insulating strips is in the region of 25-35% of the total height of the strips.

IPC 8 full level

**E06B 3/263** (2006.01)

CPC (source: EP US)

**E06B 3/2632** (2013.01 - EP US); **E06B 2003/26329** (2013.01 - EP US); **E06B 2003/26359** (2013.01 - EP US)

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)

**EP 1170454 A2 20020109; EP 1170454 A3 20021009; EP 1170454 B1 20080716;** AT E401485 T1 20080815; CA 2352720 A1 20020108; DE 10033388 A1 20020124; DE 50114114 D1 20080828; DK 1170454 T3 20081117; EP 1980701 A1 20081015; EP 1980701 B1 20130515; ES 2309019 T3 20081216; PL 203962 B1 20091130; PL 348476 A1 20020114; PT 1170454 E 20081024; US 2002046539 A1 20020425

DOCDB simple family (application)

**EP 01112511 A 20010523;** AT 01112511 T 20010523; CA 2352720 A 20010709; DE 10033388 A 20000708; DE 50114114 T 20010523; DK 01112511 T 20010523; EP 08160394 A 20010523; ES 01112511 T 20010523; PL 34847601 A 20010705; PT 01112511 T 20010523; US 90146501 A 20010709