

Title (en)

Secured high-energy electro-pyrotechnic initiator

Title (de)

Elektro-pyrotechnischer Anzünder mit gesicherter Hochenergiezündung

Title (fr)

Initiateur électro-pyrotechnique sécurisé a haute énergie

Publication

**EP 1172628 A3 20020410 (FR)**

Application

**EP 01401888 A 20010713**

Priority

FR 0009243 A 20000713

Abstract (en)

[origin: US6502512B2] The slapper type initiator comprises essentially: a connector unit (2) having two connection pins (3, 4), a first dielectric foil (5) with two drilled holes (6, 7), with a fuse (8) formed on the rear face of this first dielectric foil, a second dielectric foil (9) on the front face of which there are formed two metal pads (10, 11) facing said holes, a perforated plate (12) and a body (13) containing a pyrotechnic charge 14. The assembly is hermetically sealed. The first foil introduces a galvanic discontinuity that ensures a well-defined firing voltage, with a value high enough to prevent induced parasitic currents.

IPC 1-7

**F42B 3/12**

IPC 8 full level

**F42B 3/12** (2006.01)

CPC (source: EP US)

**F42B 3/124** (2013.01 - EP US)

Citation (search report)

- [X] EP 0482969 A2 19920429 - SCHLUMBERGER LTD [US], et al
- [XA] US 5347929 A 19940920 - LERCHE NOLAN C [US], et al
- [A] US 4441427 A 19840410 - BARRETT JOSEPH A F [US]
- [A] US 5969286 A 19991019 - WARD MICHAEL A [US], et al
- [A] US 5431104 A 19950711 - BARKER JAMES M [US]

Cited by

EP3217141A1; EP3121552A1; US9995560B2

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)

**EP 1172628 A2 20020116; EP 1172628 A3 20020410; EP 1172628 B1 20041201**; AT E284015 T1 20041215; DE 60107499 D1 20050105; DE 60107499 T2 20051208; FR 2811749 A1 20020118; FR 2811749 B1 20030307; US 2002023567 A1 20020228; US 6502512 B2 20030107

DOCDB simple family (application)

**EP 01401888 A 20010713**; AT 01401888 T 20010713; DE 60107499 T 20010713; FR 0009243 A 20000713; US 90277601 A 20010712