

Title (en)

LOW VOLTAGE RE-ENTERABLE SPLICE ENCLOSURE

Title (de)

WIEDER ZUGÄNGLICHE NIEDERSPANNUNGSMHÜLLUNG FÜR DRAHTSPLEISS

Title (fr)

BOITIER FAIBLE TENSION POUR EPISSURE REOUVRABLE

Publication

EP 1173913 B1 20031029 (EN)

Application

EP 99942061 A 19990810

Priority

- US 9918073 W 19990810
- US 30170799 A 19990429

Abstract (en)

[origin: WO0067354A1] A re-enterable enclosure (10) for protecting a cable splice includes a first cover member (12), a second cover member (14), and a splice fixation member (16). The first and second cover members are configured to releasably engage each other and form a cavity (16, 20) for enclosing the cable splice. The cavity is filled with a sealant material (50, 52) for electrically insulating the cable splice and protecting the cable splice from the environment. The cable splice is attached to the fixation member and the cover members are closed around the fixation member and attached splice.

IPC 1-7

H02G 15/10

IPC 8 full level

H01R 4/70 (2006.01); **H02G 1/14** (2006.01); **H02G 15/08** (2006.01); **H02G 15/10** (2006.01); **H02G 15/113** (2006.01); **H02G 15/18** (2006.01)

CPC (source: EP US)

H02G 15/10 (2013.01 - EP US); **H02G 15/113** (2013.01 - EP US); **H02G 15/18** (2013.01 - EP US)

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

WO 0067354 A1 20001109; AU 5552199 A 20001117; BR 9917274 A 20020423; BR 9917274 B1 20120110; CA 2371741 A1 20001109; CA 2371741 C 20070313; DE 69912481 D1 20031204; DE 69912481 T2 20040812; EP 1173913 A1 20020123; EP 1173913 B1 20031029; JP 2002543753 A 20021217; JP 4175777 B2 20081105; US 6169250 B1 20010102

DOCDB simple family (application)

US 9918073 W 19990810; AU 5552199 A 19990810; BR 9917274 A 19990810; CA 2371741 A 19990810; DE 69912481 T 19990810; EP 99942061 A 19990810; JP 2000616101 A 19990810; US 30170799 A 19990429