

Title (en)

Heat treatment of nickel-base superalloy die inserts

Title (de)

Wärmebehandlung von Matriceinsätzen bestehend aus Superlegierungen auf Nickel-Basis

Title (fr)

Traitement thermique d'un insert de matrice en superalliages à base de Ni

Publication

**EP 1176222 A2 20020130 (EN)**

Application

**EP 01305605 A 20010627**

Priority

- US 21560100 P 20000630
- US 82512801 A 20010403

Abstract (en)

A rigid die insert for forming and shaping a working material comprises a nickel-base superalloy, preferably Rene 95. A plurality of gamma prime particles are uniformly distributed throughout the rigid die insert, which has a Rockwell hardness Rc of between about 48 and about 52. The invention also includes a method of treating a rigid die insert comprising a nickel-base superalloy to reduce crack propagation and raise yield stress. The method comprises the steps of: providing the rigid die insert; dissolving larger gamma-prime particles in the rigid die insert; and growing additional gamma-prime particles of smaller particle size in the rigid die insert, whereby the particle size of each of the plurality of gamma-prime particles is refined, thereby reducing crack propagation and raising the yield stress of the rigid die insert. A method of refining the particle size of gamma-prime particles in a Rene 95 superalloy is also disclosed.

IPC 1-7

**C22F 1/10**

IPC 8 full level

**B21C 3/02** (2006.01); **C22F 1/10** (2006.01)

CPC (source: EP US)

**B21C 3/02** (2013.01 - EP US); **C22F 1/10** (2013.01 - EP US)

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

**EP 1176222 A2 20020130**; **EP 1176222 A3 20020306**; CA 2351153 A1 20011230; US 2002139458 A1 20021003

DOCDB simple family (application)

**EP 01305605 A 20010627**; CA 2351153 A 20010621; US 82512801 A 20010403