

Title (en)

SEALING OF SUCTION CASING ON THE PISTON SIDE DURING A VACUUM DIE-CASTING METHOD

Title (de)

KOLBENSEITIGE ABSAUGABDICHTUNG BEI ANWENDUNG DES VAKUUMDRUCKGIESSVERFAHRENS

Title (fr)

ETANCHEIFICATION DU CHASSIS D'ASPIRATION COTE PISTON LORS DE LA MISE EN OEUVRE DU PROCEDE DE COULEE SOUS PRESSION SOUS VIDE

Publication

EP 1177058 A1 20020206 (DE)

Application

EP 00916814 A 20000310

Priority

- DE 0000764 W 20000310
- DE 19921496 A 19990508

Abstract (en)

[origin: DE19921496A1] One of the basic pre-requisites for using the vacuum die-casting method is that said method takes place in a circuit which is sealed off from the exterior. Appropriately secure sealing systems are required, in order to avoid undesired air penetrations. According to the invention, the area between a plunger (8) and a suction casing (13) is sealed. The plunger has at least two different diameters D1 and D2, whereby the smaller diameter D2 is located at the rear end of the plunger. A sealing element (11) which corresponds to the D2 diameter is provided in the suction casing (13).

IPC 1-7

B22D 17/14; **B22D 17/20**

IPC 8 full level

B22D 17/14 (2006.01); **B22D 17/20** (2006.01)

CPC (source: EP US)

B22D 17/14 (2013.01 - EP US)

Citation (search report)

See references of WO 0067935A1

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

DE 19921496 A1 20001109; DE 50001278 D1 20030327; EP 1177058 A1 20020206; EP 1177058 B1 20030219; JP 2002543982 A 20021224; US 6749005 B1 20040615; WO 0067935 A1 20001116

DOCDB simple family (application)

DE 19921496 A 19990508; DE 0000764 W 20000310; DE 50001278 T 20000310; EP 00916814 A 20000310; JP 2000616949 A 20000310; US 95914701 A 20011018