

Title (en)

METHOD FOR SEALING THE INGOT-MOULD/DUMMY-BAR ASSEMBLY IN A CONTINUOUS-CASTING PLANT, AND CORRESPONDING SEAL ELEMENT

Title (de)

VERFAHREN ZUM ABDICHTEN DER KOKILLEN/ANFAHRSTRANG-ANORDNUNG EINER STRANGGIESSANLAGE UND ENTSPRECHENDES DICHTUNGSELEMENT

Title (fr)

PROCEDE POUR ETANCHEIFIER L'ENSEMBLE LINGOTIERE/FAUSSE BARRE D'UNE INSTALLATION DE COULEE EN CONTINU, ET ELEMENT D'ETANCHEIFICATION CORRESPONDANT

Publication

EP 1194254 B1 20030827 (EN)

Application

EP 00935181 A 20000607

Priority

- EP 0005221 W 20000607
- IT MI991295 A 19990610

Abstract (en)

[origin: WO0076693A1] In a continuous-casting plant, a method of utilization of the sealing gasket between the dummy bar and the ingot mould envisages a seal element to be installed directly within the ingot mould outside of the continuous-casting plant. Said seal element (1) may be either in the form of a slightly deformable single sheet, or in the form of a rigid plate bearing along the entire edge a plurality of deformable detached parts (10) making up a continuous gasket.

IPC 1-7

B22D 11/08

IPC 8 full level

B22D 11/08 (2006.01)

CPC (source: EP)

B22D 11/088 (2013.01)

Cited by

WO2009073005A1

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT

DOCDB simple family (publication)

WO 0076693 A1 20001221; AT E248039 T1 20030915; AU 5076200 A 20010102; AU 765130 B2 20030911; CN 1221346 C 20051005; CN 1354702 A 20020619; DE 60004848 D1 20031002; DE 60004848 T2 20040708; EP 1194254 A1 20020410; EP 1194254 B1 20030827; ES 2204609 T3 20040501; IT MI991295 A0 19990610; IT MI991295 A1 20001210

DOCDB simple family (application)

EP 0005221 W 20000607; AT 00935181 T 20000607; AU 5076200 A 20000607; CN 00808711 A 20000607; DE 60004848 T 20000607; EP 00935181 A 20000607; ES 00935181 T 20000607; IT MI991295 A 19990610