

Title (en)

PROCESS FOR TREATING CRUDE OIL

Title (de)

VERFAHREN ZUR BEHANDLUNG VON ROHÖL

Title (fr)

PROCEDE DE RAFFINAGE DE PETROL BRUT

Publication

**EP 1199347 A1 20020424 (EN)**

Application

**EP 00925681 A 20000516**

Priority

- JP 0003125 W 20000516
- JP 13548199 A 19990517

Abstract (en)

The present invention provides a method of treating a crude oil comprising a step of separating the crude oil by distillation where the crude oil is separated by distillation into a distillate oil and a heavy oil content, a step of thermal cracking where the heavy oil content separated at said step of separating the crude oil by distillation and obtained substantially from the bottom is thermally cracked to lighten the content, and a step of separating the thermal cracking product by distillation where the thermal cracking product obtained by lightening at said step of thermal cracking is separated by distillation; wherein said step of separating the crude oil by distillation and step of separating the thermal cracking product by distillation are carried out, at the same time, in a distilling section comprising a vacuum distillation apparatus. Accordingly, it is possible to simplify the process and save the space, and thereby to reduce a cost for the treatment. In addition, the method is also applicable to a small-scale refining of petroleum.  
<IMAGE>

IPC 1-7

**C10G 55/02; C10G 7/06; C10G 9/00**

IPC 8 full level

**C10G 9/00** (2006.01); **C10G 55/02** (2006.01)

CPC (source: EP)

**C10G 9/00** (2013.01); **C10G 55/02** (2013.01)

Cited by

RU2707188C2; RU2495084C1

Designated contracting state (EPC)

DE FR GB NL

DOCDB simple family (publication)

**EP 1199347 A1 20020424; EP 1199347 A4 20030502; EP 1199347 B1 20041215**; CN 100419046 C 20080917; CN 1351643 A 20020529;  
DE 60016755 D1 20050120; DE 60016755 T2 20051201; JP 4564176 B2 20101020; WO 0069992 A1 20001123

DOCDB simple family (application)

**EP 00925681 A 20000516**; CN 00807697 A 20000516; DE 60016755 T 20000516; JP 0003125 W 20000516; JP 2000618400 A 20000516