

Title (en)

Opening rollers for open-end spinning machines

Title (de)

Auflösewalze für eine Offenend-Spinnvorrichtung

Title (fr)

Cylindre peigneur pour des machines de filature à bout libre

Publication

EP 1203836 A1 20020508 (DE)

Application

EP 01117636 A 20010724

Priority

DE 10054697 A 20001104

Abstract (en)

The roller to loosen sliver and break it down into fibers, at an open-end spinner, has a clothing ring (2) which can be exchanged easily through a torque-free rapid clamp (7). The ring can be fitted to and removed from the free rotating component of the sliver loosening roller (1), powered by a drive (4). The sliver loosening roller, at an open-end spinner, has an electro drive as an outer rotor. The clothing ring is locked to the free rotating outer rotor (3) of the electro drive by the rapid clamp. The rapid clamp has two eccentric grips (26), which act on an end disk (5) of the roller through a plate spring (8), to hold the clothing ring in a force fit. Each eccentric grip has an eccentric grip body (19) and a manual release strap (18). The eccentric grips are linked to a bolt (14) of the rapid clamp system through a swing axis (17) which, in turn, has a bayonet fitting at the outer rotor. The bolt has radially projecting connectors (15), which match axial and spiral grooves in the hollow cylindrical shoulder piece of the outer rotor. Or the bolt has axial and spiral grooves, which match radial projections at the hollow cylinder shoulder piece of the outer rotor. The manual operating strap shrouds the eccentric clips, in the working condition, in a center recess (25) of the roller end disk. The clothing ring and the roller end disk form a single unit for mounting to the roller.

Abstract (de)

Die Erfindung betrifft eine Auflösewalze (1) für eine Offenend-Spinnvorrichtung mit einem lösbar festgelegten Garniturring (2). Erfindungsgemäß ist vorgesehen, daß der Garniturring (2) mittels einer drehmomentfreien Schnellspannvorrichtung (7) leicht auswechselbar an einem rotierbar gelagerten Bauteil einer durch einen Auflösewalzenantrieb (4) beaufschlagbaren Auflösewalze (1) festlegbar ist. <IMAGE>

IPC 1-7

D01H 4/32; **D01H 1/244**

IPC 8 full level

D01H 1/244 (2006.01); **D01H 4/32** (2006.01)

CPC (source: EP US)

D01H 1/244 (2013.01 - EP US); **D01H 4/32** (2013.01 - EP US)

Citation (search report)

- [XAY] DE 2752591 A1 19790531 - REINERS & FUERST
- [DY] DE 4036017 A1 19910725 - RIETER AG MASCHF [CH]
- [A] US 4196496 A 19800408 - BURCKHARDT CHRISTOPH [CH], et al
- [A] US 5689946 A 19971125 - SCHMID FRIEDBERT [DE]
- [A] US 4715177 A 19871229 - STAHLECKER FRITZ [DE]

Designated contracting state (EPC)

CH DE IT LI TR

DOCDB simple family (publication)

EP 1203836 A1 20020508; **EP 1203836 B1 20040929**; CN 1242107 C 20060215; CN 1353216 A 20020612; CZ 20013847 A3 20020612; DE 10054697 A1 20020508; DE 50103852 D1 20041104; TR 200402576 T4 20041122; US 2002053847 A1 20020509; US 6691502 B2 20040217

DOCDB simple family (application)

EP 01117636 A 20010724; CN 01132554 A 20010904; CZ 20013847 A 20011025; DE 10054697 A 20001104; DE 50103852 T 20010724; TR 200402576 T 20010724; US 93101 A 20011102