

Title (en)  
Alignment of tape head

Title (de)  
Bandkopfausrichtung

Title (fr)  
Alignement de tête pour bande

Publication  
**EP 1204096 B1 20080604 (EN)**

Application  
**EP 01308762 A 20011015**

Priority  
US 69164600 A 20001017

Abstract (en)  
[origin: EP1204096A2] A device for precision alignment of a write element (41) of a tape head (10) to a transport direction T of a media (20) that is transported across the tape head (10) is disclosed. The tape head (10) includes at least one alignment element (31) that is cofabricated with the write element (41) so that both the write element (41) and the alignment element (31) have a fixed orientation with respect to a magnetic axis M of the tape head (10). The alignment element (31) and the write element (41) can be fabricated on the tape head (10) using standard microelectronic photolithographic processes. Preferably, the tape head (10) includes a plurality of alignment elements (31). Those alignment elements (31) are operative to write alignment transitions (33) onto the media (20). The alignment transitions (33) can be observed to determine if they are indicative of the write element (41) having a predetermined orientation beta with respect to the transport direction T. A read transducer (60) can be used to generate signals (S1, S2) from the alignment transitions (33) and those signals (S1, S2) can be analyzed to determine if the predetermined orientation beta of the write element (41) has been achieved. The tape head (10) can include horizontal and/or vertical elements (61, 71) for a gross visual alignment of the tape head (10) to the media (20). The alignment transitions (33) can be read by a data element (81) of a separate data head (70). A signal from the data element (S1, S2) can be used to adjust the azimuth psi of the data head (70) with respect to a direction of transport T. In servo writer applications where servo code is prerecorded on the media, the alignment transitions (33) can be used to align the write elements of a servo write head to the transport direction of the media so that inter band skew between adjacent servo bands is significantly reduced. <IMAGE>

IPC 8 full level  
**G11B 5/008** (2006.01); **G11B 5/29** (2006.01); **G11B 5/48** (2006.01); **G11B 5/56** (2006.01); **G11B 5/58** (2006.01); **G11B 5/584** (2006.01)

CPC (source: EP KR US)  
**G11B 5/008** (2013.01 - KR); **G11B 5/4893** (2013.01 - EP US); **G11B 5/56** (2013.01 - EP US); **G11B 5/584** (2013.01 - EP US);  
**G11B 5/00826** (2013.01 - EP US)

Cited by  
US7864487B2; US9007712B1; US9916860B2; US7379258B2; US9721601B2; WO2009136374A3; WO03069600A1; WO2014164183A1;  
US8810957B1; US8902528B1; US8797682B1; US9715886B2; US9607639B2; US9754616B2

Designated contracting state (EPC)  
DE GB NL

DOCDB simple family (publication)  
**EP 1204096 A2 20020508**; **EP 1204096 A3 20030528**; **EP 1204096 B1 20080604**; CN 1294558 C 20070110; CN 1357879 A 20020710;  
DE 60134301 D1 20080717; HK 1046982 A1 20030130; JP 2002183923 A 20020628; JP 3920071 B2 20070530; KR 100830794 B1 20080520;  
KR 20020030722 A 20020425; US 2004109257 A1 20040610; US 6700729 B1 20040302; US 6898045 B2 20050524

DOCDB simple family (application)  
**EP 01308762 A 20011015**; CN 01133959 A 20010817; DE 60134301 T 20011015; HK 02108547 A 20021126; JP 2001317591 A 20011016;  
KR 20010063792 A 20011016; US 69164600 A 20001017; US 72375703 A 20031126