

Title (en)
KEY

Title (de)
DRUCKTASTE

Title (fr)
TOUCHE

Publication
EP 1206786 A1 20020522 (DE)

Application
EP 00956097 A 20000726

Priority
• DE 0002450 W 20000726
• DE 19940386 A 19990825

Abstract (en)
[origin: WO0115188A1] The invention relates to a key. Sliding cylinders (8) which run parallel to the longitudinal axis of the key, are attached by reinforcing ribs (7) to the exterior of a plunger (3) that projects axially from the underside of the key cap (1), in such a way that they lie outside the spring element (11) which acts against the plunger when the key is depressed, thus extending the guided distance into longitudinal guides (30), located in a shaft-shaped guide opening (28) of the housing (27). The key cap is secured in the housing from being detached by snap hooks (10) that are separate from the plunger, which engage in snap-in openings (31, 32). Keys of this type can be used on keyboards.

IPC 1-7
H01H 13/70

IPC 8 full level
H01H 13/70 (2006.01)

CPC (source: EP)
H01H 13/70 (2013.01); **H01H 2009/0077** (2013.01); **H01H 2221/026** (2013.01); **H01H 2221/058** (2013.01); **H01H 2221/06** (2013.01); **H01H 2233/034** (2013.01); **H01H 2237/006** (2013.01)

Citation (search report)
See references of WO 0115188A1

Cited by
US10809809B2

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
WO 0115188 A1 20010301; AT E251333 T1 20031015; CN 1169174 C 20040929; CN 1371523 A 20020925; DE 19940386 A1 20010405; DE 19940386 C2 20020814; DE 50003934 D1 20031106; EP 1206786 A1 20020522; EP 1206786 B1 20031001; TW 466518 B 20011201

DOCDB simple family (application)
DE 0002450 W 20000726; AT 00956097 T 20000726; CN 00812062 A 20000726; DE 19940386 A 19990825; DE 50003934 T 20000726; EP 00956097 A 20000726; TW 89117057 A 20000902