

Title (en)  
Blanket for offset printing

Title (de)  
Drucktuch für Offset-Druck-Anwendungen

Title (fr)  
couverture pour l'impression offset

Publication  
**EP 1208997 A1 20020529 (DE)**

Application  
**EP 00125775 A 20001124**

Priority  
EP 00125775 A 20001124

Abstract (en)  
An offset printing blanket is used in the reproduction of surface structures liable to damage under cylinder pressure. The blanket has a base layer (1) in contact with the print cylinder, an intermediate compressible layer (2) incorporating fine gas pores (5), and an outer layer (3) in contact with the print web. Under compression during the print run the compressible (2) and contact layers (3) spread to cover and effect uniform pressure on the print web surface. The compressible layer has closed pores. Under a calibration pressure of 1350 kPa the compressible layer reduces in thickness by 20-50 per cent i.e. 0.45 to 0.9 mm. The printing blanket is pref. 2.5 to 3.0 mm thick. The compressible layer is 1-2 mm thick. The ratio of outer layer to intermediate layer thickness is in the range 1: 2.5 to 1:7. The outer layer has a Shore hardness of 55 ShA. The compensation layer (7) incorporates a fabric with stretch factor of more than 7 per cent under a load of 500N/5cm.

Abstract (de)  
Die Erfindung betrifft ein Drucktuch für Offset-Druck-Anwendungen, vorzugsweise für den Einsatz zum Bedrucken von oberflächenstrukturierten und insbesondere deformationsgefährdeten Druckmaterialien, mit einer dem Druckzylinder zugeordneten Basisschicht (1), einer kompressiblen, Gaseinschlüsse (5) aufweisenden Zwischenschicht (2) und mit einer außenliegenden, dem Bedruckmaterial zugewandten Außenschicht (3). Erfindungsgemäß sind die kompressible Zwischenschicht (2) und die dem Bedruckmaterial zugewandte Außenschicht (3) derart dimensioniert, dass die beim Druckvorgang auf das Drucktuch wirkende Kraft zu einer Verformung des Verbundes aus kompressibler Zwischenschicht (2) und Außenschicht (3) dahingehend führt, dass eine vollflächige Auflage des Drucktuches auf dem Bedruckmaterial sowie eine gleichförmige Verteilung des lokalen Druckes erreicht wird. <IMAGE>

IPC 1-7  
**B41N 10/02**; **B41N 10/04**

IPC 8 full level  
**B41N 10/02** (2006.01); **B41N 10/04** (2006.01)

CPC (source: EP US)  
**B41N 10/02** (2013.01 - EP US); **B41N 10/04** (2013.01 - EP US); **B41N 2210/02** (2013.01 - EP US); **B41N 2210/04** (2013.01 - EP US); **B41N 2210/06** (2013.01 - EP US); **B41N 2210/14** (2013.01 - EP US)

Citation (search report)  
• [X] US 3983287 A 19760928 - GOOSSEN CHARLES G, et al  
• [X] US 5478637 A 19951226 - TOMONO SEIJI [JP], et al

Cited by  
EP2319690A3; ITMI20131918A1; EP1669210A3; EP1669211A3; EP1525997A1; WO2015074908A1

Designated contracting state (EPC)  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)  
**EP 1208997 A1 20020529**; **EP 1208997 B1 20050525**; AT E296207 T1 20050615; DE 50010411 D1 20050630; JP 2002166678 A 20020611; US 2002062753 A1 20020530

DOCDB simple family (application)  
**EP 00125775 A 20001124**; AT 00125775 T 20001124; DE 50010411 T 20001124; JP 2001351114 A 20011116; US 99201401 A 20011126