

Title (en)
COMMINUTING MACHINE

Title (de)
ZERKLEINERUNGSMASCHINE

Title (fr)
BROYEUSE

Publication
EP 1210178 A1 20020605 (DE)

Application
EP 00953160 A 20000805

Priority
• DE 19943518 A 19990911
• EP 0007612 W 20000805

Abstract (en)
[origin: US7108210B1] A comminution machine has a machine housing and a closed working cylinder with comminution holes arranged therein. Tools are arranged on a coaxial shaft within the working cylinder. The tools have vanes revolving at a spacing of at most a diameter of the comminution holes practically contactless relative to the cylinder. The vanes have outer edges slanted counter to a relative rotational direction between cylinder and tools. The shaft orientation and the axial orientation of the cylinder deviate from a vertical line. The working cylinder has a first end face opening connected to a feed channel and a lower cylinder half connected to a removal channel. A second end face opening whose diameter is at least as large as the greatest diameter of the working cylinder, is closed by a freely accessible lid. The shaft extends from the feed channel to the lid but does not penetrate the lid.

IPC 1-7
B02C 19/20

IPC 8 full level
B02C 19/20 (2006.01)

CPC (source: EP US)
B02C 19/20 (2013.01 - EP US)

Citation (search report)
See references of WO 0119524A1

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
US 7108210 B1 20060919; AT E270152 T1 20040715; DE 19943518 A1 20010322; DE 19943518 B4 20040805; DE 50006975 D1 20040805; EP 1210178 A1 20020605; EP 1210178 B1 20040630; WO 0119524 A1 20010322

DOCDB simple family (application)
US 8802904 A 20041110; AT 00953160 T 20000805; DE 19943518 A 19990911; DE 50006975 T 20000805; EP 0007612 W 20000805; EP 00953160 A 20000805