

Title (en)

METHOD AND DEVICE FOR REFURBISHING THE LEAKY WALLS OF CONDUITS HAVING SMALL DIAMETERS

Title (de)

VERFAHREN UND VORRICHTUNG ZUM SANIEREN DER UNDICHTEN WÄNDE VON ROHRLEITUNGEN MIT KLEINEN DURCHMESSERN

Title (fr)

PROCEDE ET DISPOSITIF POUR RENOVER DES PAROIS NON ETANCHES DE CANALISATIONS DE FAIBLE DIAMETRE

Publication

**EP 1210543 A1 20020605 (DE)**

Application

**EP 00956268 A 20000725**

Priority

- DE 19943200 A 19990909
- DE 19955439 A 19991118
- EP 0007089 W 20000725

Abstract (en)

[origin: WO0118444A1] The invention relates to a method for refurbishing the leaky walls of horizontal, vertical or inclined conduits having small diameters up to a nominal diameter of approximately DN 200. Refurbishing is carried out by introducing a fibre tube that is impregnated with a UV-hardenable resin into the conduit. The tube is mounted, preferably under pressure, in such a way that said tube rests on the inner wall of the conduit. One or more UV-light sources are led through. UV-light is emitted from the light sources and onto the fibre tube, whereby the resin is hardened. An artificial resin, especially a styrene-free epoxy acrylate resin, that does not limit the functions of thermoplastic inner films is used for impregnating the fibre tube.

IPC 1-7

**F16L 55/165**

IPC 8 full level

**B29C 63/00** (2006.01); **F16L 55/165** (2006.01); **F16L 55/26** (2006.01); **B29C 35/08** (2006.01); **B29C 63/34** (2006.01)

CPC (source: EP)

**B29C 63/0021** (2013.01); **B29C 63/0069** (2013.01); **F16L 55/1654** (2013.01); **F16L 55/26** (2013.01); **B29C 63/34** (2013.01); **B29C 2035/0827** (2013.01); **F16L 2101/00** (2013.01)

Citation (search report)

See references of WO 0118444A1

Designated contracting state (EPC)

AT CH DE FR LI SE

DOCDB simple family (publication)

**WO 0118444 A1 20010315**; EP 1210543 A1 20020605

DOCDB simple family (application)

**EP 0007089 W 20000725**; EP 00956268 A 20000725