

Title (en)
STATOR WITH RIGID RETAINING RING

Title (de)
STATOR MIT STABILEM STIRNRING

Title (fr)
STATOR AVEC ANNEAU FRONTAL RIGIDE

Publication
EP 1222396 B1 20041222 (DE)

Application
EP 00978972 A 20001005

Priority
• DE 0003491 W 20001005
• DE 19950258 A 19991018

Abstract (en)
[origin: US6666668B1] On an eccentric screw pump or an eccentric screw motor, both the outer wall and the inner wall of the jacket (21) have a helicoid form. In order to stabilise the cross-sectional profile of the jacket (21) in the vicinity of the ends and to allow it to be simply coupled to the other housing sections (5, 6), a retaining ring (28) sits on each end of the jacket (21). The retaining ring contains a through channel (32), whose cross-sectional surface has a form which substantially corresponds to the cross-sectional surface that is delimited by the inner wall (23) or outer wall (24).

IPC 1-7
F04C 2/107

IPC 8 full level
F04C 2/107 (2006.01)

CPC (source: EP US)
F04C 2/1075 (2013.01 - EP US)

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
US 6666668 B1 20031223; AT E285521 T1 20050115; DE 19950258 A1 20010426; DE 50009059 D1 20050127; EP 1222396 A1 20020717; EP 1222396 B1 20041222; ES 2231285 T3 20050516; WO 0129422 A1 20010426

DOCDB simple family (application)
US 11097302 A 20020418; AT 00978972 T 20001005; DE 0003491 W 20001005; DE 19950258 A 19991018; DE 50009059 T 20001005; EP 00978972 A 20001005; ES 00978972 T 20001005