

Title (en)  
CRANKPIN GRINDING METHOD

Title (de)  
VERFAHREN ZUM SCHLEIFEN VON KURBELZAPFEN

Title (fr)  
PROCEDE DE RECTIFICATION DE MANETON

Publication  
**EP 1224057 A1 20020724 (EN)**

Application  
**EP 00971591 A 20001026**

Priority  
• GB 0004135 W 20001026  
• GB 9925367 A 19991027  
• GB 9925487 A 19991028

Abstract (en)  
[origin: WO0130534A2] A method is disclosed in which a component is rotated by a headstock during grinding, and wherein metal is removed in a conventional way until shortly before finish size is achieved and thereafter the component is rotated through only one revolution during a finish grinding step, and the depth of cut and the headstock velocity are controlled during that signal rotation, so as to maintain a substantially constant load on the grinding wheel spindle drive motor. Preferably the depth of cut is kept constant and the component speed of rotation is altered in order to maintain the constant power requirement, without exceeding the maximum power capability of the spindle motor. If the component profile alters the spindle loading during a single revolution, the component speed is altered from one point to another during each revolution so as to maintain the constant load. In another method, a component is rotated by a headstock during grinding to finish size, wherein the headstock velocity is linked to the power capabilities of the grinding wheel spindle drive, and a significant grinding force is maintained between the wheel and the component up to the end of the grinding process including during finish grinding, thereby to achieve a significant depth of cut even during the finish grinding step, for the purpose of reducing chatter and grind marks on the final finished surface and/or achieve even wear around the grinding wheel, and to achieve a short grind time. A computer is programmed to control headstock acceleration and deceleration and velocity and to take into account of any variation in contact length between the wheel and component during the rotation of the latter, so that although the metal removal rate may vary slightly around the circumference of the component the power demand on the spindle motor is maintained substantially constant during the whole of the grinding of the component. Grinding is preferably performed using a small diameter wheel.  
[origin: WO0130534A2] A method is disclosed in which the component is rotated through only one revolution during a finish grinding step, and the depth of cut and the headstock (12) velocity are controlled during the signal rotation, so as to maintain a substantially constant load on the grinding wheel spindle drive motor (28, 30). Preferably the depth of cut is kept constant and the component speed of rotation is altered in order to maintain the constant power requirement, without exceeding the maximum power capability of the spindle motor. The component speed is altered from one point to another during each revolution so as to maintain the constant load. In another method, the headstock (12) velocity is linked to the power capabilities of the grinding wheel spindle drive (28, 30), and a significant grinding force is maintained between the wheel and the component up to the end of the grinding process including during finish grinding.

IPC 1-7  
**B24B 1/00; B24B 5/42; B24B 51/00**

IPC 8 full level  
**B24B 1/00** (2006.01); **B24B 5/42** (2006.01); **B24B 19/12** (2006.01); **B24B 27/00** (2006.01); **B24B 49/00** (2012.01); **B24B 49/16** (2006.01)

CPC (source: EP US)  
**B24B 1/00** (2013.01 - EP US); **B24B 5/42** (2013.01 - EP US); **B24B 19/125** (2013.01 - EP US); **B24B 27/0076** (2013.01 - EP US); **B24B 49/00** (2013.01 - EP US); **B24B 49/16** (2013.01 - EP US)

Citation (search report)  
See references of WO 0130536A1

Cited by  
CN111546139A; CN103286662A

Designated contracting state (EPC)  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)  
**WO 0130534 A2 20010503; WO 0130534 A3 20020510**; CA 2380560 A1 20010503; CA 2383908 A1 20010503; CA 2384988 A1 20010503; CA 2388426 A1 20010503; DE 60002497 D1 20030605; DE 60002497 T2 20040325; DE 60003835 D1 20030814; DE 60003835 T2 20040527; DE 60007542 D1 20040205; DE 60007542 T2 20041223; DE 60018778 D1 20050421; DE 60018778 T2 20050901; DE 60030790 D1 20061026; DE 60030790 T2 20070111; EP 1224056 A1 20020724; EP 1224056 B1 20050316; EP 1224057 A1 20020724; EP 1224057 B1 20030709; EP 1224058 A2 20020724; EP 1224058 B1 20040102; EP 1224059 A1 20020724; EP 1224059 B1 20030502; EP 1473113 A1 20041103; EP 1473113 B1 20060913; ES 2198356 T3 20040201; ES 2202183 T3 20040401; ES 2214328 T3 20040916; ES 2239620 T3 20051001; ES 2268543 T3 20070316; GB 0026256 D0 20001213; GB 0026257 D0 20001213; GB 0026258 D0 20001213; GB 0026259 D0 20001213; GB 2357719 A 20010704; GB 2357719 B 20030604; GB 2357720 A 20010704; GB 2357720 B 20030507; GB 2357721 A 20010704; GB 2357721 B 20030716; GB 2357722 A 20010704; GB 2357722 B 20030507; MX PA02004136 A 20021017; MX PA02004139 A 20021017; MX PA02004140 A 20021011; US 2005026548 A1 20050203; US 2005032466 A1 20050210; US 6682403 B1 20040127; US 6767273 B1 20040727; US 6808438 B1 20041026; US 6811465 B1 20041102; US 7153194 B2 20061226; US 7297046 B2 20071120; WO 0130535 A1 20010503; WO 0130536 A1 20010503; WO 0130537 A1 20010503

DOCDB simple family (application)  
**GB 0004136 W 20001026**; CA 2380560 A 20001026; CA 2383908 A 20001026; CA 2384988 A 20001026; CA 2388426 A 20001026; DE 60002497 T 20001026; DE 60003835 T 20001026; DE 60007542 T 20001026; DE 60018778 T 20001026; DE 60030790 T 20001026; EP 00969713 A 20001026; EP 00969715 A 20001026; EP 00971591 A 20001026; EP 00971592 A 20001026; EP 04013436 A 20001026; ES 00969713 T 20001026; ES 00969715 T 20001026; ES 00971591 T 20001026; ES 00971592 T 20001026; ES 04013436 T 20001026; GB 0004126 W 20001026; GB 0004130 W 20001026; GB 0004135 W 20001026; GB 0026256 A 20001026; GB 0026257 A 20001026; GB 0026258 A 20001026; GB 0026259 A 20001026; MX PA02004136 A 20001026; MX PA02004139 A 20001026; MX PA02004140 A 20001026;

US 11163902 A 20020426; US 11164002 A 20020829; US 11164102 A 20020426; US 11164202 A 20020426; US 93616704 A 20040908;  
US 93629104 A 20040908