

Title (en)
AIR CONDITIONER

Title (de)
KLIMAAANLAGE

Title (fr)
CLIMATISEUR

Publication
EP 1227286 A4 20030507 (EN)

Application
EP 00969980 A 20001023

Priority
• JP 0007369 W 20001023
• JP 30854499 A 19991029

Abstract (en)
[origin: EP1227286A1] A reheat drying operation is conducted such that a refrigerant from a compressor 2 is circulated in the order of an outdoor heat exchanger 3, a depressurizing mechanism 4 and an indoor heat exchanger 5, while a first heat exchanger 10 and a second heat exchanger 11 are allowed to function as a condenser and an evaporator, respectively, in order to cool and dehumidify indoor air, then to reheat and return the air indoors. At this time, temperature of the second heat exchanger 11 functioning as an evaporator is controlled by a control means 13. Consequently, even when the interior of a room is slightly heated while dehumidified, a dehumidifying amount is increased by controlling temperature of the evaporator, and thus a reheat drying operation can be reliably conducted. <IMAGE>

IPC 1-7
F25B 29/00; F24F 11/02; F24F 3/14; F24F 3/153

IPC 8 full level
F25B 29/00 (2006.01); **F24F 1/0063** (2019.01); **F24F 1/0083** (2019.01); **F24F 3/153** (2006.01); **F25B 13/00** (2006.01)

CPC (source: EP KR US)
F24F 1/0057 (2019.01 - EP); **F24F 1/0063** (2019.01 - EP US); **F24F 1/0083** (2019.01 - EP US); **F24F 3/153** (2013.01 - EP); **F25B 13/00** (2013.01 - EP); **F25B 39/02** (2013.01 - KR); **F25B 49/02** (2013.01 - KR); **F25B 2313/0234** (2013.01 - EP); **F25B 2313/02341** (2013.01 - EP); **F25B 2313/02343** (2013.01 - EP); **F25B 2313/02344** (2013.01 - EP); **F25B 2313/0254** (2013.01 - KR); **F25B 2700/02** (2013.01 - KR); **F25B 2700/2104** (2013.01 - KR)

Citation (search report)
• [X] US 5231845 A 19930803 - SUMITANI SHIGETO [JP], et al
• [A] US 5345776 A 19940913 - KOMAZAKI MEGUMI [JP], et al
• [A] US 5678417 A 19971021 - NIGO TOSHIRO [JP], et al
• [A] EP 0560037 A1 19930915 - TOSHIBA KK [JP]
• [XY] PATENT ABSTRACTS OF JAPAN vol. 1997, no. 02 28 February 1997 (1997-02-28)
• [Y] PATENT ABSTRACTS OF JAPAN vol. 1997, no. 05 30 May 1997 (1997-05-30)
• [Y] PATENT ABSTRACTS OF JAPAN vol. 1999, no. 14 22 December 1999 (1999-12-22)
• [X] PATENT ABSTRACTS OF JAPAN vol. 017, no. 271 (M - 1417) 26 May 1993 (1993-05-26)
• [A] PATENT ABSTRACTS OF JAPAN vol. 017, no. 312 (M - 1429) 15 June 1993 (1993-06-15)
• [A] PATENT ABSTRACTS OF JAPAN vol. 1995, no. 04 31 May 1995 (1995-05-31)
• See references of WO 0133146A1

Cited by
EP2040009A4; DE102017109552A1; EP3282198A1; CN107726444A; US7886556B2; EP3282199A1; CN107726492A; CN112797657A

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
EP 1227286 A1 20020731; EP 1227286 A4 20030507; EP 1227286 B1 20090225; AT E423949 T1 20090315; AU 7953600 A 20010514; CN 1196902 C 20050413; CN 1384910 A 20021211; DE 60041649 D1 20090409; ES 2321685 T3 20090610; JP 2001124434 A 20010511; KR 100491718 B1 20050525; KR 20020070973 A 20020911; WO 0133146 A1 20010510

DOCDB simple family (application)
EP 00969980 A 20001023; AT 00969980 T 20001023; AU 7953600 A 20001023; CN 00814935 A 20001023; DE 60041649 T 20001023; ES 00969980 T 20001023; JP 0007369 W 20001023; JP 30854499 A 19991029; KR 20027005192 A 20020423