

Title (en)

Connector assembly for connecting an expansion vessel

Title (de)

Anschlussarmatur zum Anschliessen eines Druckausdehnungs-Gefäßes

Title (fr)

Armature de connexion pour vase d'expansion

Publication

EP 1239230 A1 20020911 (DE)

Application

EP 02012827 A 19970610

Priority

- EP 02012827 A 19970610
- EP 97250179 A 19970610

Abstract (en)

The pressure expansion tank is divided by a membrane into a water-filled hollow compartment, and a pressurized gas-filled chamber. The connecting fitment incorporates a suction arrangement creating suction causing water exchange over a flow path with forward (96) and backward (94) paths formed by coaxial ducts. A molded body (26) has a middle part (30) containing an inner duct (46) as part of the backward path and protruding into the water-flow. an outer duct (42) of the molded body as part of the forward path is connected to the water flow by means of an inlet extending round the middle part.

Abstract (de)

Die Erfindung betrifft eine Anschlußarmatur zum Anschließen eines Druckausdehnungs-Gefäßes an ein Leitungssystem, in welchem eine Wasserströmung fließt, wobei eine Membran das Gefäß in einen mit Wasser gefüllten Hohlraum und einen mit einem Druckgas gefüllten Druckgasraum unterteilt, bei welcher die Armatur eine Sogeinrichtung enthält, in welcher durch die Wasserströmung ein Sog erzeugbar ist, mittels dieses Sogs eine Wasseraustausch-Strömung über einen zu der Wasserströmung parallelen, durch den Hohlraum verlaufenden Strömungsweg mit einem Vorlaufweg und einem Rücklaufweg erzeugbar ist. Der parallele Strömungsweg ist durch ein Kükenventil absperrenbar. Zur Vereinfachung der Konstruktion sind Vorlauf- und Rücklaufweg (96;94) von zueinander coaxialen Kanälen gebildet. Dabei ist der Vorlaufweg (96) von dem äußeren der coaxialen Kanäle und der Rücklaufweg (94) von dem inneren der coaxialen Kanäle gebildet. Ein Formkörper (26) ragt mit einem inneren Kanal (46) als Teil des Rücklaufweges (94) enthaltenden Mittelteil (30) in die Wasserströmung hinein. Der innere Kanal (46) des Formkörpers (26) ist an seinem auslaßseitigen Ende in Richtung parallel zu der Wasserströmung abgewinkelt. Ein äußerer Kanal (42) des Formkörpers (26) steht als Teil des Vorlaufweges (96) über eine sich um den Mittelteil (30) erstreckende einlaßseitige Einlaßöffnung mit der Wasserströmung in Verbindung.

<IMAGE>

IPC 1-7

F24D 3/10

IPC 8 full level

F24D 3/10 (2006.01)

CPC (source: EP US)

E03B 7/075 (2013.01 - EP US); **F24D 3/1008** (2013.01 - EP US); **F24D 3/1041** (2013.01 - EP US); **Y10T 137/86726** (2015.04 - EP US)

Citation (search report)

- [A] DE 8507703 U1 19850801
- [E] DE 19609375 C1 19970612 - OTTO HEAT HEIZUNGS [DE]
- [A] DE 29621353 U1 19970206 - REFLEX WINKELMANN & PANNHOFF G [DE]

Citation (examination)

- DE 19529959 A1 19970220 - REFLEX WINKELMANN & PANNHOFF G [DE]
- EP 0602430 A1 19940622 - SASSERATH & CO KG H [DE]

Designated contracting state (EPC)

AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)

EP 0884539 A1 19981216; EP 0884539 B1 20030423; AT E238523 T1 20030515; DE 59709918 D1 20030528; DK 0884539 T3 20030811; EP 1239230 A1 20020911; ES 2197299 T3 20040101; PT 884539 E 20030930; US 5988218 A 19991123

DOCDB simple family (application)

EP 97250179 A 19970610; AT 97250179 T 19970610; DE 59709918 T 19970610; DK 97250179 T 19970610; EP 02012827 A 19970610; ES 97250179 T 19970610; PT 97250179 T 19970610; US 9548098 A 19980610