

Title (en)
Printing method

Title (de)
Druckverfahren

Title (fr)
Méthode d'impression

Publication
EP 1243414 B1 20070411 (DE)

Application
EP 02003008 A 20020212

Priority
DE 10114250 A 20010322

Abstract (en)
[origin: EP1243414A1] The rotary printing machine comprises several printing cylinders (18,20) which can be placed against, and removed from the print by means of a regulator (32). A control periodically stops and starts at least one (20) of the printing cylinders during operation and within a time-span less than the time the printing cylinder takes to revolve, between the start and stop position. Each of the printing cylinders has its own motor on the axle of the printing cylinder.

IPC 8 full level
B41F 5/14 (2006.01); **B41F 5/24** (2006.01); **B41M 1/04** (2006.01)

CPC (source: EP US)
B41F 5/24 (2013.01 - EP US); **B41P 2217/52** (2013.01 - EP US)

Citation (examination)
US 4628816 A 19861216 - SIX ALBERT J [US]

Cited by
EP1852256A1; WO2006134070A3; US11485101B2; US11911992B2; US10642551B2; US11807480B2; US11449290B2; US11520544B2; US11907595B2

Designated contracting state (EPC)
DE ES FR GB IT

DOCDB simple family (publication)
EP 1243414 A1 20020925; EP 1243414 B1 20070411; EP 1243414 B2 20141224; DE 10114250 A1 20020926; DE 50209888 D1 20070524; ES 2283476 T3 20071101; ES 2283476 T5 20150220; JP 2002326441 A 20021112; US 2002134267 A1 20020926; US 6796226 B2 20040928

DOCDB simple family (application)
EP 02003008 A 20020212; DE 10114250 A 20010322; DE 50209888 T 20020212; ES 02003008 T 20020212; JP 2002081043 A 20020322; US 9066102 A 20020305