

Title (en)  
Bolt fitting

Title (de)  
Riegelbeschlag

Title (fr)  
Ferrure avec tige de verrouillage

Publication  
**EP 1255005 B1 20030730 (DE)**

Application  
**EP 01110623 A 20010430**

Priority  
EP 01110623 A 20010430

Abstract (en)  
[origin: EP1255005A1] Lock (10) for doors, windows, etc. comprises a rosette body (60) fixed on a door or window leaf, a rotating handle (12) axially fixed with a handle neck (18) on the rosette body, and a lock part (80) arranged on the door or window frame. On operating the handle a locking element (40) at least partly engages with holding surfaces (104) in the lock part. The locking element is a stud protruding perpendicularly from the handle neck and inserted with its head (46) into a locking nut (84) of the lock part in which it is clamped in two directions running at an angle to each other. Preferred Features: The locking bolt is screwed into a radial stepped bore (32) of an insert (30) which sits in a fixed manner in the handle neck.

IPC 1-7  
**E05B 13/10**; **E05B 15/02**

IPC 8 full level  
**E05B 13/10** (2006.01); **E05B 15/02** (2006.01); **E05C 3/04** (2006.01); **E05B 63/12** (2006.01); **E05B 63/14** (2006.01)

CPC (source: EP)  
**E05B 13/106** (2013.01); **E05B 15/025** (2013.01); **E05C 3/043** (2013.01); **E05B 63/12** (2013.01); **E05B 63/14** (2013.01)

Cited by  
EP1503015A3; EP3819445A1

Designated contracting state (EPC)  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)  
**EP 1255005 A1 20021106**; **EP 1255005 B1 20030730**; AT E246300 T1 20030815; DE 50100442 D1 20030904; DK 1255005 T3 20031110

DOCDB simple family (application)  
**EP 01110623 A 20010430**; AT 01110623 T 20010430; DE 50100442 T 20010430; DK 01110623 T 20010430