

Title (en)
METHOD AND DEVICE FOR DETECTING A NO_x CONCENTRATION OF AN EXHAUST GAS STREAM PERTAINING TO A COMBUSTION ENGINE

Title (de)
VERFAHREN UND VORRICHTUNG ZUR BESTIMMUNG EINER NO_x-KONZENTRATION EINES ABGASSTROMES EINER VERBRENNUNGSKRAFTMASCHINE

Title (fr)
PROCEDE ET DISPOSITIF POUR DETERMINER LA CONCENTRATION DE NO_x DANS LE COURANT DE GAZ D'ECHAPPEMENT D'UN MOTEUR A COMBUSTION INTERNE

Publication
EP 1255917 B1 20051116 (DE)

Application
EP 01909650 A 20010118

Priority
• DE 10003228 A 20000126
• EP 0100540 W 20010118

Abstract (en)
[origin: WO0155565A2] The invention relates to a method and a device for detecting a NO_x concentration of an exhaust gas stream of a combustion engine by means of a NO_x-sensitive measuring device, especially a NO_x sensor, that is arranged downstream in relation to a NO_x storage catalyst in an exhaust gas section of the combustion engine. According to the invention, a search for a minimum (min) of a signal curve (SK) pertaining to the measuring device (18) is carried out in an operational phase of the combustion engine (10), whereby the NO_x concentration passes through a value close to zero on the position of the NO_x-sensitive measuring device (18) during said phase. The detected minimum (min) is taken over as the zero point for calibrating the measuring device (18).
[origin: WO0155565A2] The invention relates to a method and a device for detecting a NO_x concentration of an exhaust gas stream of a combustion engine by means of a NO_x-sensitive measuring device, especially a NO_x sensor, that is arranged downstream in relation to a NO_x storage catalyst in an exhaust gas section of the combustion engine. According to the invention, a search for a minimum (min) of a signal curve (SK) pertaining to the measuring device (18) is carried out in an operational phase of the combustion engine (10), whereby the NO_x concentration passes through a value close to zero on the position of the NO_x-sensitive measuring device (18) during said phase. The detected minimum (min) is taken over as the zero point for calibrating the measuring device (18).

IPC 1-7
F01N 1/00

IPC 8 full level
F02D 41/14 (2006.01); **F02D 41/24** (2006.01)

CPC (source: EP)
F02D 41/146 (2013.01); **F02D 41/2441** (2013.01); **F02D 41/2474** (2013.01)

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
WO 0155565 A2 20010802; **WO 0155565 A3 20020110**; AU 3731801 A 20010807; DE 10003228 A1 20010906; DE 50108081 D1 20051222; EP 1255917 A2 20021113; EP 1255917 B1 20051116

DOCDB simple family (application)
EP 0100540 W 20010118; AU 3731801 A 20010118; DE 10003228 A 20000126; DE 50108081 T 20010118; EP 01909650 A 20010118