

Title (en)

Weft insertion control apparatus in jet loom

Title (de)

Schussfadeneintragskontrollvorrichtung in eine Düsenwebmaschine

Title (fr)

Dispositif de contrôle de l'insertion de trame dans un métier à jet

Publication

EP 1258550 A3 20030205 (EN)

Application

EP 02009374 A 20020506

Priority

- JP 2001141576 A 20010511
- JP 2002015613 A 20020124

Abstract (en)

[origin: EP1258550A2] A distance L1 between a rotation axis 222 of a stepping motor 22 and a first guide ring 24 is made shorter than a distance L2 between the rotation axis 222 and a second guide ring 25. When weft Y1 is on a second yarn route, that is, when a yarn route changing body 23 is in a weft braking position, a yarn bending angle alpha becomes larger than a yarn bending angle beta . <IMAGE>

IPC 1-7

D03D 47/34; B65H 59/26

IPC 8 full level

B65H 59/26 (2006.01); **D03D 47/34** (2006.01)

CPC (source: EP KR)

B65H 59/26 (2013.01 - EP); **D03D 47/34** (2013.01 - EP KR); **B65H 2701/31** (2013.01 - EP)

Citation (search report)

- [AD] EP 0527510 A1 19930217 - PICANOL NV [BE]
- [AD] JP S60185844 A 19850921 - HANDA KENJIROU

Cited by

BE1016285A3; BE1018921A5; ITTO20120156A1; EP2631339A1; EP1783255A1; EP3165646A3

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)

EP 1258550 A2 20021120; EP 1258550 A3 20030205; EP 1258550 B1 20060712; CN 1225577 C 20051102; CN 1385568 A 20021218;
KR 100482533 B1 20050414; KR 20020086288 A 20021118; TW 565637 B 20031211

DOCDB simple family (application)

EP 02009374 A 20020506; CN 02119318 A 20020509; KR 20020025761 A 20020510; TW 91109763 A 20020510