

Title (en)
Ink-jet head and ink-jet printing apparatus

Title (de)
Tintenstrahlkopf und Tintenstrahldruckapparat

Title (fr)
Tête à jet d'encre et appareil d'impression à jet d'encre

Publication
EP 1260372 A3 20021218 (EN)

Application
EP 02015089 A 19980903

Priority

- EP 98116674 A 19980903
- JP 23977397 A 19970904
- JP 24689097 A 19970911

Abstract (en)
[origin: EP0900659A2] In order to enable high speed printing with maintaining reliability of ink ejection, an auxiliary hole (13) is provided in an upper wall (15) forming a liquid passage. An opening area of the auxiliary hole is set to be greater than or equal to three times of an opening area of an ejection opening (12), and a minimum distance (L4) between the auxiliary hole (13) and the ejection opening (12) is set to be greater than or equal to three times of a height (H1) of the liquid passage (14). <IMAGE>

IPC 1-7
B41J 2/14

IPC 8 full level
B41J 2/14 (2006.01); **B41J 2/15** (2006.01)

CPC (source: EP US)
B41J 2/1404 (2013.01 - EP US); **B41J 2/1433** (2013.01 - EP US); **B41J 2/15** (2013.01 - EP US); **B41J 2002/14169** (2013.01 - EP US);
B41J 2002/14387 (2013.01 - EP US)

Citation (search report)

- [A] EP 0465071 A
- [A] US 4550326 A 19851029 - ALLEN ROSS R [US], et al
- [A] US 5317346 A 19940531 - GARCIA ANDRE [US]

Cited by
US7625080B2; US9452605B2; CN102105306A; EP2212116A4; EP1607222A1; EP2209638A4; WO2009067730A1; US9126411B2;
WO2009145759A1; TWI411539B; US9868289B2; US10232623B2; WO2009055528A2

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 0900659 A2 19990310; EP 0900659 A3 19991229; EP 0900659 B1 20021211; DE 69810037 D1 20030123; DE 69810037 T2 20030430;
DE 69833050 D1 20060202; DE 69833050 T2 20060803; EP 1260372 A2 20021127; EP 1260372 A3 20021218; EP 1260372 B1 20051228;
US 6280020 B1 20010828

DOCDB simple family (application)
EP 98116674 A 19980903; DE 69810037 T 19980903; DE 69833050 T 19980903; EP 02015089 A 19980903; US 14445098 A 19980901