Title (en)
Shutter device

Title (de)
Verschlusseinrichtung

Title (fr)
Dispositif à volet

Publication
EP 1260668 A3 20030108 (EN)

Application
EP 02011202 A 20020521

Priority
IL 14324601 A 20010520

Abstract (en)
[origin: EP1260668A2] It is provided a shutter assembly for an aperture, comprising: a plurality of adjacent elongate slats (20) coupled together to form a slat assembly, said slats (20) having: a lower edge; a lower channel (38) along the lower edge, said lower channel (38) being defined by at least one inwardly directed lower lip (40,42); an upper edge; and at least one upper channel (52) along at least part of the upper edge, said upper channel each being defined by at least one inwardly directed upper lip (34,36); wherein said slats (20) are coupled to an adjacent slat (20) in the shutter assembly by at least two coupling linkages (44), said coupling linkages (44) having upper and lower hooked heads (46,46'); and wherein said inwardly directed lips (34,36; 40,42)and said hooked heads (46,46') are mutually configured such that said upper hooked heads (46) are captured within the lower channel (38) of an adjacent slat (20) by said at least one lower lip (40,42), and said lower hooked heads (46') are captured within the at least one upper channel (52) of an adjacent slat (20) by said at least one upper lip (34,36). <IMAGE>

IPC 1-7
E06B 9/165

IPC 8 full level
E06B 9/165 (2006.01)

CPC (source: EP)
E06B 9/165 (2013.01)

Citation (search report)
• [XY] FR 1508003 A 19671229
• [Y] DE 7441951 U

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)
EP 1260668 A2 20021127; EP 1260668 A3 20030108; EP 1260668 B1 20050302; AT E290153 T1 20050315; DE 60203062 D1 20050407; DE 60203062 T2 20060323; ES 2236390 T3 20050716; IL 143246 A0 20020421; IL 143246 A 20040620

DOCDB simple family (application)
EP 02011202 A 20020521; AT 02011202 T 20020521; DE 60203062 T 20020521; ES 02011202 T 20020521; IL 14324601 A 20010520