

Title (en)  
EXTERIOR MOLD

Title (de)  
FORMMANTEL

Title (fr)  
SURMOULE

Publication  
**EP 1261465 B1 20040811 (DE)**

Application  
**EP 01925374 A 20010305**

Priority  
• DE 10010917 A 20000306  
• EP 0102469 W 20010305

Abstract (en)

[origin: US2003164438A1] A securing device comprising at least one latch (22) and at least one latch mating-element (26) are used on two mutually displaceable mold-casing segments (14, 16) to close or open a mold casing (10) used in manufacturing molded bodies, in particular concrete pipes, said device securing the mold casing (10) in a position of manufacture. The latch (22) is displaceable by means of a drive unit (24) between a locked position wherein it locks up with a latch mating-element (26) and an unlocked position wherein no locking takes place between the latch (22) and the latch mating-element (26). In the invention, the drive unit (24) can be adjusted due to relative motions between the mold casing on one hand and its manufacturing environment on the other as determined by the manufacturing procedures between a ready-to-unlock position corresponding to the locked position of the latch (22) and a ready-to-lock position corresponding to the locked position.

IPC 1-7  
**B28B 7/00; B28B 21/82**

IPC 8 full level  
**B28B 7/00** (2006.01); **B28B 21/82** (2006.01)

CPC (source: EP US)  
**B28B 7/0014** (2013.01 - EP US); **B28B 7/0044** (2013.01 - EP US); **B28B 21/82** (2013.01 - EP US)

Designated contracting state (EPC)  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)

**US 2003164438 A1 20030904; US 6997429 B2 20060214;** AT E273114 T1 20040815; AU 5215701 A 20010917; DE 10010917 A1 20010913; DE 50103221 D1 20040916; EP 1261465 A1 20021204; EP 1261465 B1 20040811; ES 2225521 T3 20050316; PT 1261465 E 20041130; TR 200402438 T4 20041221; WO 0166326 A1 20010913

DOCDB simple family (application)

**US 22081203 A 20030115;** AT 01925374 T 20010305; AU 5215701 A 20010305; DE 10010917 A 20000306; DE 50103221 T 20010305; EP 0102469 W 20010305; EP 01925374 A 20010305; ES 01925374 T 20010305; PT 01925374 T 20010305; TR 200402438 T 20010305