

Title (en)

DIRECT PRINTING APPARATUS AND METHOD

Title (de)

GERÄT UND VERFAHREN ZUM DIREKTEN DRUCKEN

Title (fr)

APPAREIL ET PROCEDE D'IMPRESSION DIRECTE

Publication

EP 1261490 A1 20021204 (EN)

Application

EP 00973321 A 20001020

Priority

SE 0002031 W 20001020

Abstract (en)

[origin: WO0232679A1] An image forming apparatus and a method for direct printing in which an image information is converted into a pattern of electrostatic fields for modulating a transport of charged toner particles from a particle carrier towards an image receiving surface. A printhead structure is arranged in the background electric field, including a plurality of apertures and control electrodes arranged in conjunction to the apertures. A plurality of the printhead structures (3005', 3005'', 3005''', 3005''''') and the particle carriers (3033', 3033'', 3033''', 3033''''') are arranged in a succession along the image receiving surface (3001). Each printhead structure has a particle-emitting plane at a printing distance (l_i' , l_i'' , l_i''' , l_i'''') from the image receiving surface (3001) for selectively permitting or restricting transport of charged toner particles of a specific color. The printing distance (l_i'''') of a later printhead structure (3005''''') is at least mu m larger than the printing distance (l_i') of an earlier printhead structure (3005') in the succession.

IPC 1-7

B41J 2/415; G03G 15/34

IPC 8 full level

B41J 2/415 (2006.01); **G03G 15/01** (2006.01); **G03G 15/34** (2006.01)

CPC (source: EP)

B41J 2/4155 (2013.01); **G03G 15/0142** (2013.01); **G03G 15/0194** (2013.01); **G03G 15/346** (2013.01); **G03G 2217/0025** (2013.01)

Citation (search report)

See references of WO 0232679A1

Designated contracting state (EPC)

DE GB

DOCDB simple family (publication)

WO 0232679 A1 20020425; AU 1184401 A 20020429; EP 1261490 A1 20021204

DOCDB simple family (application)

SE 0002031 W 20001020; AU 1184401 A 20001020; EP 00973321 A 20001020