

Title (en)
Switch device

Title (de)
Schaltvorrichtung

Title (fr)
Dispositif de commutation

Publication
EP 1263008 A2 20021204 (EN)

Application
EP 02011968 A 20020529

Priority
JP 2001165796 A 20010531

Abstract (en)
The switch device is provided with a first switch comprising a first fixed side contact, a conductor plate having a first movable side contact brought into or out of contact with the first fixed side contact, and a spring member for slidably supporting the conductor plate onto a central terminal; a second switch comprising a second fixed side contact, and a second movable side contact brought into or out of contact with the second fixed side contact; a sliding member for displacing the first movable side contact and the second movable side contact; and a case with the first switch and the second switch built into it, wherein the second movable side contact is formed of a twisted coil spring having arms in contact with a pair of fixed terminals. <IMAGE>

IPC 1-7
H01H 13/56; H01H 9/00; H01H 1/24

IPC 8 full level
H01H 13/64 (2006.01); **H01H 3/12** (2006.01); **H01H 9/00** (2006.01); **H01H 13/56** (2006.01); **H01H 1/24** (2006.01)

CPC (source: EP)
H01H 9/0066 (2013.01); **H01H 1/245** (2013.01); **H01H 13/562** (2013.01)

Cited by
EP3312861A1; US2018114655A1; US10707031B2

Designated contracting state (EPC)
DE FR GB IT NL

DOCDB simple family (publication)
EP 1263008 A2 20021204; **EP 1263008 A3 20040506**; **EP 1263008 B1 20090624**; CN 1215506 C 20050817; CN 1400616 A 20030305; DE 60232700 D1 20090806; JP 2002358850 A 20021213; JP 4030730 B2 20080109

DOCDB simple family (application)
EP 02011968 A 20020529; CN 02122227 A 20020530; DE 60232700 T 20020529; JP 2001165796 A 20010531