

Title (en)
SECURITY SEAL TO BE PULLED THROUGH

Title (de)
DURCHZIEH-SICHERHEITSPLOMBE

Title (fr)
FERMETURE DE SECURITE A LANGUETTE TRAVERSANTE

Publication
EP 1266370 B1 20090218 (DE)

Application
EP 00908905 A 20000323

Priority
CH 0000168 W 20000323

Abstract (en)
[origin: WO0171699A1] The invention relates to a security seal to be pulled through. The inventive seal comprises a base body (1) and a tongue (2) which protrudes therefrom and can be inserted through a pull-through opening (7) that is arranged in a housing component (3) being connected to the base body (1). A restraint inset (4) is arranged in the housing component (3). The tongue (2) is provided with toes (6) which protrude towards the outside in a rectangular-shaped manner when seen in the cross-section. Said toes can engage with the hooks (5) in a toothed manner, whereby said hooks are arranged in the restraint inset (4). The housing component (3) is provided with an outlet (8). The cross-section of said outlet matches the cross-section of the tongue (2) comprising the toes (6). Said form practically prevents the hooks (5) from being manipulated by means of simple, flat tools. Influence or manipulation of the toothing between the toes (6) and the hooks (5) can practically be excluded.

IPC 8 full level
G09F 3/03 (2006.01); **B65D 55/02** (2006.01)

CPC (source: EP US)
G09F 3/037 (2013.01 - EP US); **Y10T 292/495** (2015.04 - EP US); **Y10T 292/499** (2015.04 - EP US); **Y10T 292/502** (2015.04 - EP US)

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

DOCDB simple family (publication)
WO 0171699 A1 20010927; AT E423370 T1 20090315; AU 3142000 A 20011003; DE 50015565 D1 20090402; EP 1266370 A1 20021218; EP 1266370 B1 20090218; US 6948747 B1 20050927

DOCDB simple family (application)
CH 0000168 W 20000323; AT 00908905 T 20000323; AU 3142000 A 20000323; DE 50015565 T 20000323; EP 00908905 A 20000323; US 23962603 A 20030205