

Title (en)

USE OF A HARDENABLE COPPER ALLOY FOR MOLDS

Title (de)

VERWENDUNG EINER AUSHÄRTBAREN KUPFERLEGIERUNG FÜR KOKILLEN

Title (fr)

UTILISATION D'UN CUPRO-ALLIAGE DURCISSABLE PAR VIEILLISSEMENT POUR COQUILLES

Publication

EP 1274871 A1 20030115 (DE)

Application

EP 01929554 A 20010412

Priority

- DE 10018504 A 20000414
- EP 0104235 W 20010412

Abstract (en)

[origin: WO0179574A1] The invention relates to the use of a hardenable copper alloy containing 0.1 % to 0.5 % beryllium and 0.5 % to 2.0 % nickel for the production of broad side plates for thin slab continuous casting molds at casting speeds of at least 2 to 6 m/min and higher.

IPC 1-7

C22C 9/06; **B22D 11/06**

IPC 8 full level

B22D 11/06 (2006.01); **B22D 11/059** (2006.01); **C22C 9/06** (2006.01)

CPC (source: EP KR US)

B22D 11/059 (2013.01 - EP US); **C22C 9/06** (2013.01 - EP KR US)

Citation (search report)

See references of WO 0179574A1

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)

WO 0179574 A1 20011025; CN 1423707 A 20030611; DE 10018504 A1 20011018; EG 22980 A 20031231; EP 1274871 A1 20030115; JP 2003531290 A 20031021; KR 20020091154 A 20021205; RU 2260493 C2 20050920; TW 524864 B 20030321; US 2003165396 A1 20030904; US 2005158204 A1 20050721

DOCDB simple family (application)

EP 0104235 W 20010412; CN 01808026 A 20010412; DE 10018504 A 20000414; EG 20010361 A 20010411; EP 01929554 A 20010412; JP 2001576957 A 20010412; KR 20027012659 A 20020925; RU 2002130502 A 20010412; TW 90108247 A 20010406; US 25751203 A 20030402; US 7800605 A 20050311