

Title (en)
EXTINGUISHER

Title (de)
LÖSCHGERÄT

Title (fr)
MATÉRIEL DE LUTTE ANTI-INCENDIE

Publication
EP 1278577 B1 20031112 (DE)

Application
EP 01935999 A 20010426

Priority
• DE 0101574 W 20010426
• DE 10021511 A 20000503

Abstract (en)
[origin: WO0183032A2] The invention relates to an extinguisher which comprises a pressurised-gas generator for fighting fires and incipient explosions. Said extinguisher has two rupture diaphragms comprising predetermined breaking points for sealing the container of the extinguisher. According to the invention, the predetermined breaking points of the rupture diaphragms have different resistances, in order to introduce a temporal delay between the ruptures of the two predetermined breaking points. This enables the extinguishing agent to be discharged in an even, rotationally symmetrical manner.

IPC 1-7
A62C 35/02; **A62C 19/00**

IPC 8 full level
A62C 19/00 (2006.01); **A62C 35/02** (2006.01)

CPC (source: EP US)
A62C 19/00 (2013.01 - EP US); **A62C 35/023** (2013.01 - EP US)

Cited by
CN107050702A

Designated contracting state (EPC)
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)
WO 0183032 A2 20011108; **WO 0183032 A3 20020404**; AT E253958 T1 20031115; CZ 20023540 A3 20030312; DE 10021511 A1 20011115; DE 10021511 B4 20040318; DE 50100970 D1 20031218; EP 1278577 A2 20030129; EP 1278577 B1 20031112; HU P0300448 A2 20030628; SK 15442002 A3 20030401; US 2003173093 A1 20030918; US 6769492 B2 20040803

DOCDB simple family (application)
DE 0101574 W 20010426; AT 01935999 T 20010426; CZ 20023540 A 20010426; DE 10021511 A 20000503; DE 50100970 T 20010426; EP 01935999 A 20010426; HU P0300448 A 20010426; SK 15442002 A 20010426; US 25853502 A 20021023