

Title (en)  
Drop door seal

Title (de)  
Absenkbare Türdichtung

Title (fr)  
Joint d'étanchéité descendant pour porte

Publication  
**EP 1279791 A1 20030129 (DE)**

Application  
**EP 02405604 A 20020715**

Priority  
CH 13782001 A 20010724

Abstract (en)  
The door seal, at the foot of the door, is lowered when the door is closed and raised when the door is opened. It has a profiled guide rail (2) and a sliding sealing bar (3) with a plastics or metal carrier profile rail (30), a lower sealing lip (31) and side sealing lips (32). When the door is closed, the lower sealing lip is against the floor surface (B). The side sealing lips slide against the inner walls (20) of the profiled guide rail, and are shaped at the carrier profile preferably by co-extrusion. Acoustic dampers (33) are at the ends of the legs (34) of the carrier profile rail.  
The door seal, at the foot of the door, is lowered when the door is closed and raised when the door is opened. It has a profiled guide rail (2) and a sliding sealing bar (3) with a plastics or metal carrier profile rail (30), a lower sealing lip (31) and side sealing lips (32). When the door is closed, the lower sealing lip is against the floor surface (B). The side sealing lips slide against the inner walls (20) of the profiled guide rail, and are shaped at the carrier profile preferably by co-extrusion. Acoustic dampers (33) are at the ends of the legs (34) of the carrier profile rail.

Abstract (de)  
Eine absenkbare Türdichtung weist eine Führungsprofilschiene (2) und eine in der Führungsprofilschiene (2) verschiebbaren Dichtleiste (3) auf, wobei die Dichtleiste (3) eine Trägerprofilschiene (30), eine untere Dichtlippe (31) und seitliche Dichtlippen (32) umfasst. Die untere Dichtlippe (31) liegt im geschlossenen Zustand der Türe (1) am Boden (B) an. Die seitlichen Dichtlippen (32) liegen gleitend an Innenwänden (20) der Führungsprofilschiene (2) an und sind seitlich an der Trägerprofilschiene (30) angeformt, vorzugsweise sind sie koextrudiert. Diese Absenkdichtung ist einfach herstellbar, kostengünstig und relativ schmal, ermöglicht jedoch trotzdem eine dreifache Dichtung. <IMAGE>

IPC 1-7  
**E06B 7/215**

IPC 8 full level  
**E06B 7/215** (2006.01)

CPC (source: EP)  
**E06B 7/215** (2013.01)

Citation (search report)  
• [X] EP 1085162 A2 20010321 - HAHN GMBH & CO KG DR [DE]  
• [DXA] US 3453780 A 19690708 - THOMPSON EDWIN R  
• [DY] EP 0338974 A2 19891025 - PLANET MATTHIAS JAGGI [CH]  
• [DXY] PATENT ABSTRACTS OF JAPAN vol. 1998, no. 14 31 December 1998 (1998-12-31)

Cited by  
EP1347146A3; EP1460232A1; DE102016103180A1; DE102016103180B4; EP2378050B1; EP3241974B1

Designated contracting state (EPC)  
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SK TR

DOCDB simple family (publication)  
**EP 1279791 A1 20030129; EP 1279791 B1 20080416**; AT E392530 T1 20080515; DE 50212095 D1 20080529; ES 2304425 T3 20081016

DOCDB simple family (application)  
**EP 02405604 A 20020715**; AT 02405604 T 20020715; DE 50212095 T 20020715; ES 02405604 T 20020715