

Title (de)

Verfahren zum Befördern von Bogen in einem Anleger einer Bogen verarbeitenden Druckmaschine

Publication

**EP 1281647 A9 20041222 (DE)**

Application

**EP 02014920 A 20020708**

Priority

DE 10137536 A 20010801

Abstract (en)

[origin: EP1281647A2] The method involves varying the speed of the transport belt (6) independently of the working speed of the processing machine (1) according to a predefined speed profile. The transport belt is stopped and/or started in accordance with a defined acceleration profile when starting or stopping the feeder (4). The belt can be stopped or started with a predefined speed ramp with a continuous profile of speed changes over the period.

IPC 8 full level

**B65H 5/02** (2006.01); **B65H 5/22** (2006.01); **B65H 5/24** (2006.01); **B65H 5/34** (2006.01); **B65H 9/08** (2006.01); **B65H 3/08** (2006.01)

CPC (source: EP)

**B65H 3/0825** (2013.01); **B65H 5/24** (2013.01); **B65H 5/34** (2013.01); **B65H 11/005** (2013.01)

Cited by

DE102007057732A1; DE102007051945A1; DE102019122496A1; DE102019122494A1; EP1528021A1; CN101670949A; EP1352742A1; EP2135743A3; EP2065322A3; DE102015208047A1; DE102015208047B4; DE102019122495A1; US10052886B2; EP2135743A2; DE102019122496B4; WO2021032567A1; US11530102B2; DE102009034443A1; US8006975B2; EP2065322A2; US7946571B2; DE102019122494B4; EP2055657A2

DOCDB simple family (publication)

**EP 1281647 A2 20030205**; **EP 1281647 A3 20040317**; **EP 1281647 A9 20041222**; **EP 1281647 B1 20060927**; **EP 1281647 B2 20090617**; AT E340753 T1 20061015; DE 10137536 A1 20030213; DE 50208239 D1 20061109; JP 2003104582 A 20030409; JP 4105497 B2 20080625

DOCDB simple family (application)

**EP 02014920 A 20020708**; AT 02014920 T 20020708; DE 10137536 A 20010801; DE 50208239 T 20020708; JP 2002224806 A 20020801