

Title (en)

METHOD AND DEVICE FOR THE EARLY DETECTION OF FIRE AND FOR FIGHTING FIRE INDOORS AND OUTDOORS, ESPECIALLY IN LIVING AREAS, OF HOMES AND BUILDINGS

Title (de)

VERFAHREN UND VORRICHTUNG ZUM FRÜHERKENNEN UND BEKÄMPFEN VON FEUER IM INNEN- UND AUßENBEREICH, INSBESONDERE WOHNBEREICH, VON HÄUSERN UND GEBÄUDEN

Title (fr)

PROCEDE ET DISPOSITIF POUR DETECTER DE MANIERE PRECOCE ET LUTTER CONTRE LE FEU DANS DES ZONES INTERIEURES ET EXTERIEURES, NOTAMMENT DANS LA ZONE D'HABITATION DE MAISONS ET DE BATIMENTS

Publication

**EP 1286727 B1 20111116 (DE)**

Application

**EP 01929222 A 20010227**

Priority

- DE 0100809 W 20010227
- DE 10012705 A 20000308

Abstract (en)

[origin: WO0167411A2] The invention relates to a method and device for the early detection of fire and for fighting fire indoors and outdoors, especially in living areas, of homes and buildings. According to the invention, a central freely programmable domestic control block comprising an intelligent bus system, sensors, and actuators controls, regulates and monitors the domestic technical system and, at the same time, sensors detect the direct and indirect fire characteristics, which are monitored by a separate check, control and regulating block that activates an extinguishing agent supply system when a set value has been exceeded. The aim of the invention is to improve a method and device of the aforementioned type such that the extinguishing agent is variably and selectively discharged with a high degree of efficacy by the provision of a system which can be modularly integrated in the security design of a building. The extinguishing agent is variably and selectively discharged according to the origin and progression of the fire while simultaneously minimizing the water consumption, decreasing the damage caused by water in the case of a fire, and increasing the economic efficiency. To this end, the invention provides that the check, control and regulating block interactively communicates with the control block of the domestic technical system, and that an extinguishing agent supply system is actuated which integrates all available extinguishing agent sources of a house and initiates the discharge of extinguishing agent with a variable quantity and distribution according to the origin and progression of the fire.

IPC 8 full level

**A62C 37/40** (2006.01)

CPC (source: EP US)

**A62C 37/40** (2013.01 - EP US)

Citation (examination)

- DE 19627353 C1 19971023 - FEUERSCHUTZ G KNOPF GMBH [DE]
- WO 9747203 A1 19971218 - BSE ELEKTRO TECHNIK GES MBH [AT], et al

Cited by

CN106267665A

Designated contracting state (EPC)

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE TR

DOCDB simple family (publication)

**WO 0167411 A2 20010913; WO 0167411 A3 20020411**; AT E533535 T1 20111215; AU 5610301 A 20010917; DE 10012705 A1 20011011; DE 10012705 B4 20060914; EP 1286727 A2 20030305; EP 1286727 B1 20111116; US 2003038718 A1 20030227; US 6801132 B2 20041005

DOCDB simple family (application)

**DE 0100809 W 20010227**; AT 01929222 T 20010227; AU 5610301 A 20010227; DE 10012705 A 20000308; EP 01929222 A 20010227; US 22096002 A 20020905