

Title (en)  
Ink cartridge and remaining ink volume detection method

Title (de)  
Tintenpatrone und Verfahren zur Detektion der restlichen Tintenmenge

Title (fr)  
Cartouche d'encre et procédé de détection du volume d'encre restant

Publication  
**EP 1300248 A3 20070124 (EN)**

Application  
**EP 02029048 A 19990330**

Priority

- EP 99302481 A 19990330
- JP 8403798 A 19980330
- JP 9477298 A 19980407
- JP 9477398 A 19980407
- JP 9477498 A 19980407
- JP 9477598 A 19980407
- JP 9477698 A 19980407
- JP 9477798 A 19980407
- JP 9477898 A 19980407
- JP 14699398 A 19980528
- JP 16692098 A 19980615
- JP 2832099 A 19990205

Abstract (en)  
[origin: EP0947328A2] An ink cartridge has a first partitioning wall (5) and a third partitioning wall (7) for dividing the inside of a case (2) into a first ink chamber (9) and a second ink chamber (10), and a second partitioning wall (6) for demarcating an atmosphere connection chamber (11). In an upper case cover (3) are formed an ink filling hole (13) communicating with the second ink chamber (10) and a pressure reduction hole (14) communicating with the atmosphere connection chamber (11). Therefore, when ink filling is being done, the filling apparatus and the pressure reduction apparatus need only be brought to bear from one side of the upper case cover, resulting in improved work efficiency. Ink filling can be performed efficiently because the ink successively passes to the second ink chamber (10) and the first ink chamber (9). After ink filling, the ink filling hole (13) and the pressure reduction hole (14) can easily be sealed off with sealing material. An ink cartridge is thus provided that can be easily assembled at low cost. <IMAGE>

IPC 8 full level  
**B41J 2/175** (2006.01)

CPC (source: EP)  
**B41J 2/17513** (2013.01); **B41J 2/17553** (2013.01); **B41J 2/17566** (2013.01); **B41J 2002/17573** (2013.01)

Citation (search report)

- [X] JP H10787 A 19980106 - MINOLTA CO LTD
- [X] EP 0765756 A2 19970402 - CANON KK [JP]
- [X] EP 0631874 A2 19950104 - CANON KK [JP]
- [X] EP 0791464 A2 19970827 - FUJI XEROX CO LTD [JP]
- [X] EP 0542247 A2 19930519 - CANON KK [JP]
- [A] DE 4328001 A1 19950223 - DIA NIELSEN GMBH [DE]
- [A] EP 0375383 A1 19900627 - HEWLETT PACKARD CO [US]

Cited by  
EP1808298A1; US7500738B2

Designated contracting state (EPC)  
DE GB SE

DOCDB simple family (publication)  
**EP 0947328 A2 19991006; EP 0947328 A3 20000510; EP 0947328 B1 20051207**; EP 1300248 A2 20030409; EP 1300248 A3 20070124; EP 1300248 B1 20081022; EP 1300249 A2 20030409; EP 1300249 A3 20070124; EP 1300249 B1 20081022

DOCDB simple family (application)  
**EP 99302481 A 19990330**; EP 02029048 A 19990330; EP 02029049 A 19990330