

Title (en)

Electrically operated nailing device including a safety device

Title (de)

Elektrisch betriebener Nagler mit Sicherheitseinrichtung

Title (fr)

Dispositif de clouage actionné électriquement comprenant un dispositif de sécurité

Publication

**EP 1306171 B1 20050914 (DE)**

Application

**EP 02023877 A 20021024**

Priority

DE 10152063 A 20011025

Abstract (en)

[origin: EP1306171A1] In horizontal use, The motor (6) is seated on the horizontally-moving impact rod (9), in the shaft of the hollow casing (3). The motor drive shaft is guided by a recess of the firing rod (8). This has a recess on its lower side and is supported against the firing spring (2). Integrated into the handle, the spring-loaded release mechanism (1) is connected above to a safety- and thrust rod (4) with a safety spring (5). When the latter is tensioned, the spring (2) is engaged in the recess and the firing rod is arrested. The magazine casing (10) is connected low into the casing shaft, ahead of the safety- and thrust rod (4).

IPC 1-7

**B25C 1/00**; **B25C 1/06**; **B25C 5/15**

IPC 8 full level

**B25C 1/00** (2006.01); **B25C 1/06** (2006.01)

CPC (source: EP)

**B25C 1/005** (2013.01); **B25C 1/008** (2013.01); **B25C 1/06** (2013.01)

Cited by

GB2445017A

Designated contracting state (EPC)

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SK TR

DOCDB simple family (publication)

**EP 1306171 A1 20030502**; **EP 1306171 B1 20050914**; AT E304429 T1 20050915; DE 10249799 A1 20030612; DE 50204243 D1 20051020

DOCDB simple family (application)

**EP 02023877 A 20021024**; AT 02023877 T 20021024; DE 10249799 A 20021024; DE 50204243 T 20021024