

Title (en)
Printer

Title (de)
Drucker

Title (fr)
Imprimante

Publication
EP 1308304 B1 20050810 (EN)

Application
EP 02023991 A 20021025

Priority
JP 2001334877 A 20011031

Abstract (en)
[origin: EP1308304A2] **ÄPurpose** Ensuring that a suitable tension is always applied to paper fed from whichever side (front side or rear side) of a platen. **<??>ÄSolution** A first conveyor roller assembly (2) (a drive roller (21), a pressure roller (22)) and a second conveyor roller assembly (3) (a drive roller (31), a pressure roller (32)) for clampingly conveying paper are disposed at respective places upstream from and downstream from a printing station including a print head (50) and a platen (60). The paper may be conveyed via a first paper feeding passage extending from the first conveyor roller assembly (2) to the second conveyor roller assembly (3) or reversely via a second paper feeding passage extending from the second conveyor roller assembly (3) to the first conveyor roller assembly (2). The first and second conveyor roller assemblies are independently driven into rotation by separate drive motors (M1,M2) so that the circumferential speeds of these conveyor roller assemblies are readily adjusted. **<IMAGE>**

IPC 1-7
B41J 13/00; B41J 13/03

IPC 8 full level
B41J 13/02 (2006.01); **B41J 13/00** (2006.01); **B65H 5/06** (2006.01)

CPC (source: EP)
B41J 13/0027 (2013.01)

Designated contracting state (EPC)
DE FR GB

DOCDB simple family (publication)
EP 1308304 A2 20030507; EP 1308304 A3 20031203; EP 1308304 B1 20050810; DE 60205441 D1 20050915; DE 60205441 T2 20061109; JP 2003136796 A 20030514; TW I228078 B 20050221

DOCDB simple family (application)
EP 02023991 A 20021025; DE 60205441 T 20021025; JP 2001334877 A 20011031; TW 91124783 A 20021024